



SYMBOL: **4933447738** MANUFACTURER: **Milwaukee** EAN: **4002395006632**



M12 CHZ-202X - Sub compact reciprocating saw 12 V, 2.0 Ah, HACKZALL™, FUEL™, in case with 2 batteries and charger, 4933447738

- Voltage: 12 V
- Stroke length: 15,9 mm
- No load stroke rate: 0 - 3000 spm
- Vibration cutting: 5.7 m/s²
- Vibration cutting wooden beam and boards: 6.52 / 5.7 m/s²
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 2.0 Ah
- Charger supplied: 40 min
- Weight with battery pack: 1.6 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~1 689,00 zł~~ **-10%**

1 520,10 zł (tax excl.)

(1 869,72 zł (tax incl.))

PayU

Product page

link > <https://imilwauke.pl/en/20333-m12-chz-202x-sub-compact-reciprocating-saw-12-v-20-ah-hackzall-fuel...>

DESCRIPTION

- Sound power and pressure level: 93.9 / 82.9 dB(A)
- Brushless POWERSTATE™ motor for up to 6x longer motor life and up to 70% faster cutting in certain applications.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Patented FIXTEC™ clamp for fast and easy keyless blade change.
- Counter balance mechanism lowers vibration to 6.5 m/s² allowing the operator to work safely for longer periods of time reducing fatigue.
- Sealed gearbox prevents water and debris entering the housing.
- LED light illuminates the cutline in low light conditions.
- Compact and light weight allows users to complete applications in restricted areas.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#).
- Standard equipment: 1 Sawzall™ blade.
- **Supplied in case (HD Box) with 2 batteries and charger.**

FEATURES

Symbol	M12CHZ-202X
Długość skoku	15,90
Ilość akumulatorów	2
Ilość suwów	0-3000
Zasilanie	battery
Napięcie akumulatora [V]	12