




SYMBOL: **4933416860** MANUFACTURER: **Milwaukee** EAN: **4002395237807**



HD28 SX-0 - Reciprocating saw 28 V, SAWZALL™, HEAVY DUTY, without equipment, 4933416860

- Voltage: 28 V
- Stroke length: 28.6 mm
- No load stroke rate: 0-2000/0-3000 spm
- Max. cutting depth in soft-wood: 300 mm
- Max. cutting depth in steel and aluminium: 25 mm
- Max. cutting depth in non-ferrous metal: 25 mm
- Max. cutting depth in metal pipe: 150 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight: 3.2 kg
- Weight with battery pack: 4.1 kg

 **WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



Product page

link > <https://imilwauke.pl/en/20338-hd28-sx-0-reciprocating-saw-28-v-sawzall-heavy-duty-without-equipme...>



DESCRIPTION

- Vibration cutting: 16,8 m/s²
- Sound power and pressure level: 94 / 83 dB(A)
- High performance motor delivers maximum power whilst (optimising) maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Patented FIXTEC™ clamp for fast and easy keyless blade change.
- Gear protection clutch - protects the gearbox in case of blade lock ups.
- Counter balance mechanism to reduce vibrations.
- 28.6 mm stroke length, 3000 spm for extremely fast cutting.
- Tool free, adjustable shoe quickly adjusts blade depth.
- Convenient two-speed selection for best cut control in different materials.
- Soft grip gripping surfaces for maximum comfort and control.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Standard equipment: 2 SAWZALL™ blades.
- **Supplied without battery and charger.**

FEATURES

Symbol	HD28SX-0
Długość skoku	28.60
Ilość akumulatorów	brak
Ilość suwów	0-2000/0-3000
Zasilanie	battery
Napięcie akumulatora [V]	28

