






SYMBOL: 4933416860

MANUFACTURER: Milwaukee

FAN: 4002395237807

HD28 SX-0 - Reciprocating saw 28 V, SAWZALL™, HEAVY DUTY, without equipment

- · Voltage: 28 V
- Stroke length: 28.6 mm
- No load stroke rate: 0-2000/0-3000 spm
- Max. cutting depth in soft-wood: 300 mm
- Max. cutting depth in steel and aluminium: 25 mm
- Max. cutting depth in non-ferrous metal: 25 mm
- Max. cutting depth in metal pipe: 150 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- · Weight: 3.2 kg
- Weight with battery pack: 4.1 kg









link > https://imilwauke.pl/en/20338-hd28-sx-0-reciprocating-saw-28-v-sawzall-heavy-duty-without-equipme...

DESCRIPTION

- Vibration cutting: 16,8 m/s²
- Sound power and pressure level: 94 / 83 dB(A)
- High performance motor delivers maximum power whilst (optimising) maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
 Patented FIXTEC™ clamp for fast and easy keyless blade change.
- · Gear protection clutch protects the gearbox in case of blade lock ups.
- 28.6 mm stroke length, 3000 spm for extremely fast cutting.
- Tool free, adjustable shoe quickly adjusts blade depth.
 Convenient two-speed selection for best cut control in different materials.
- Soft grip gripping surfaces for maximum comfort and control.
- Fuel gauge displays remaining charge.
- REDLITHIUM*-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
 Standard equipment: 2 SAWZALL** blades.
- · Supplied without battery and charger.

FEATURES

Symbol	HD28SX-0
Długość skoku	28.60
Ilość akumulatorów	brak
Ilość suwów	0-2000/0-3000
Zasilanie	battery
Napięcie akumulatora [V]	28

