



SYMBOL: **4933451114** MANUFACTURER: **Milwaukee** EAN: **4002395137381**



## M18 BP-402C - Planer 18 V, 4.0 Ah, in case with 2 batteries and charger

- Voltage: 18 V
- No load speed: 14000 rpm
- Max. cutting depth: 2 mm
- Cutting width: 82 mm
- Rebate depth: 10.7 mm
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 4.0 Ah
- Charger supplied: 80 min
- Weight with battery pack: 2.7 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~2 629,00 zł~~ **-10%**

**2 366,10 zł** (tax excl.)

(2 910,30 zł (tax incl.))

PayU

Product page

link > [https://imilwauke.pl/en/20371-m18-bp-402c-planer-18-v-40-ah-in-case-with-2-batteries-and-charger....](https://imilwauke.pl/en/20371-m18-bp-402c-planer-18-v-40-ah-in-case-with-2-batteries-and-charger...)

### DESCRIPTION

- High performance 4-pole motor delivers 14,000 rpm to achieve optimum surface finish.
- REDLINK™ overload protection and constant speed electronics in tool deliver best in class durability and performance.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Faster material removal with two double edged carbide blades over a planing width of 82 mm.
- Adjustable depth of cut from 0 to 2 mm with twenty locking positions allows the user to accurately set the amount of material to be removed in one pass.
- Up to 10.7 mm of rebate depth.
- Left or right chip ejection allows the user to keep the chips away from his face when planing.
- Extended front shoe allows the tool to be placed on the work piece accurately and quickly.
- A kick stand located on the base protects the work piece from accidental damage.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- Standard equipment: dust bag, edge & bevel guide.
- Supplied in case (Kitbox) with 2 batteries and charger.

### FEATURES

Symbol	M18BP-402C
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Szerokość strugania	82.00
Obroty [obr/min]	14000