



SYMBOL: **4933459708** MANUFACTURER: **Milwaukee** EAN: **4058546028800**



M18 FFSDC13-0 - Standing drain cleaner with spiral 13 mm, 18 V, FUEL™, without equipment, 4933459708

- Voltage: 18 V
- No load speed: 0 - 250 rpm
- Capacity: 50 - 110 mm
- Max. drain diameter: 100 mm
- Spiral diameter: 13 mm
- Spiral length: 15 m
- Cable length: 15 m
- Sound power and pressure level: 83.4 / 72.4 dB(A)
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 13.4 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~5 829,00 zł~~ **-10%**

5 246,10 zł (tax excl.)

(6 452,70 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://imilwauke.pl/en/20512-m18-ffsdc13-0-standing-drain-cleaner-with-spiral-13-mm-18-v-fuel-wi...>

DESCRIPTION

- Brushless POWERSTATE™ motor delivers maximum power 30 m down the line.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- M18 FUEL™ SWITCH PACK™ tool-free drum connection system allows users to quickly interchange between cable sizes, or add a second drum to reach 30 m down the line.
- Built-in backpack straps for the easiest transport to any roof, drain, crawl space, or clean out.
- Integrated drum brake electronically slows drum super-fast for end user control and safety.
- Electronic foot pedal with non-slip grip for maximum durability.
- Fully enclosed drum for best protection and mess containment.
- SWITCH PACK™ drum capacity 8 mm x 23 m inner core cable.
- On-tool accessory attachment storage.
- Supplied with 1 x backpack assembly, 2 x drum assembly's, 2 x 13 mm x 15 m cables, 1 x cutter set & removal tool.
- Accepts other brand cables.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#)
- Supplied without battery and charger.

FEATURES

Symbol	M18FFSDC13-0
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	0-250