







MANUFACTURER: Milwaukee

FAN: 4002395141623

M12 BDC6-202C - Sub compact drain cleaner with spiral 6 mm, 12 V, 2.0 Ah, in bucket with 2 batteries and charger, 4933451635

- · Voltage: 12 V
- No load speed: 0 500 rpm
- Max. drain diameter: 50 mm
- Spiral diameter: 6 mm
- Spiral length: 7.6 m
- Bucket capacity: 22.5 I
- Cable length: 7.6 m
- Vibration level: 5.49 m/s²
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 2.0 Ah
- Charger supplied: 40 min
- Weight with battery pack: 4.2 kg



















1 439,10 zł (tax excl.)

(1 770,09 zł (tax incl.))

Pay**U**ⁱ **VISA** MasterCard

link > https://imilwauke.pl/en/20516-m12-bdc6-202c-sub-compact-drain-cleaner-with-spiral-6-mm-12-v-20-ah...

DESCRIPTION

- · Sound power and pressure level: 83.2 / 72.2 dB(A)
- Lightest professional drain cleaner on the market.
 Versatile design, provides benefits of both handheld and floor based drain cleaners in one machine.
- Best user flexibility and manoeuvrability due to the independence of electric power supply.
 Tool includes a highly flexible 6 mm spiral for easy access in drainpipes up to 50 mm, also all standard ø 6 & 8 mm spirals can be used with the tool.
- Robust drum shield protects user & fixtures from spinning drum during use.

 Easy removable inner drum helps to prevent spiral bind up and contains dirt inside the drum.
- Quick cable lock mechanism for manual feeding and releasing the spiral.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- REDLITHIUM**-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
 Flexible battery system: works with all MILWAUKEE® M12** batteries.
- · Supplied in bucket with 2 batteries and charger.

FFATURES

| 2.1.0.1.20 | |
|--------------------------|--------------|
| Symbol | M12BDC6-202C |
| Ilość akumulatorów | 2 |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 12 |
| Obroty [obr/min] | 0-500 |