



SYMBOL: **4933440435** MANUFACTURER: **Milwaukee** EAN: **4002395000951**



M12 GG-0 - Sub compact grease gun 12 V, without equipment, 4933440435

- Voltage: 12 V
- Pressure: 562 bar
- Sound power level: 65.5 dB(A)
- Sound pressure level: 54.5 dB(A)
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 3.2 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



919,00 zł **-10%**

827,10 zł (tax excl.)

(1 017,33 zł (tax incl.))

PayU



Product page

link > <https://imilwauke.pl/en/20521-m12-gg-0-sub-compact-grease-gun-12-v-without-equipment-4933440435.html>

DESCRIPTION

- Powerful 12 V motor delivers over 562 bar max operating pressure.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Best in class run time - dispenses up to 7 cartridges per charge.
- Superior handle balance and ergonomics - only 355 mm long and 3.2 kg.
- Air bleeder valve - priming mechanism for quick flow.
- Integrated hose storage & shoulder strap loop - added user convenience and less down time.
- Three way loading - bulk, cartridge and suction capable.
- Grease capacity 400 ml cartridge, 473 ml bulk.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#)
- Supplied with 914 mm x 14.4 mm high pressure flex hose with spring guard and grease coupler.
- Supplied **without battery and charger**.

FEATURES

Symbol	M12GG-0
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	12
Ciśnienie robocze	562.00

