



SYMBOL: **4933464814** MANUFACTURER: **Milwaukee** EAN: **4058546227593**



M18 CBLPP4B-502B - POWERPACK M18™, M18 CBLDD, HD18 AG-125, M18 BIW12, M18 BSX, 2 x 5.0 Ah + charger, in bag

NOTE: The product has been withdrawn from sale by the manufacturer. No suggested replacements available.

- Set contains:
 - M18 CBLDD - compact brushless drill drivers 18 V
 - [HD18 AG-125](#) - angle grinder 125 mm, 18 V
 - [M18 BSX](#) - reciprocating saw 18 V, SAWZALL®
 - M18 BIW12 - impact wrench 1/2"
 - [M18 B5](#) - 2 batteries 5.0 Ah
 - [M12-18C](#) - charger 100 min
- Supplied in bag



Product page

link > <https://imilwauke.pl/en/20550-m18-cblpp4b-502b-powerpack-m18-m18-cbldd-hd18-ag-125-m18-biw12-m18-...>

DESCRIPTION

M18 CBLDD

- Voltage: 18 V
- Chuck capacity: 13 mm
- Max. drilling steel / wood: 13 / 52 mm
- Max. torque: 60 Nm
- No load speed gear 1: 0 - 500 rpm
- No load speed gear 2: 0 - 1800 rpm
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 1.8 kg

- Compact brushless drill driver measuring 165 mm in length for access into tight spaces.
- Advanced 13 mm heavy duty metal chuck for quick bit changes and superior bit retention.
- 60 Nm of torque - best power to size ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- All metal reversible belt clip to hang your tool quickly and easily.
- On board fuel gauge and LED light.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

HD18 AG-125

- Voltage: 18 V
- Disc diameter: 125 mm
- Max. cutting depth: 33 mm
- No load speed: 9000 rpm
- Anti-kickback protection: No
- Line lock out function: No
- Brake: No
- Spindle size: M14
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2.2 kg

- High performance 4-pole motor delivers maximum power whilst (optimising) maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Full metal gear case delivers heavy duty durability.
- Reduced height of gear box and slim girth design deliver optimum ergonomics.
- Non-lockable switch for best user protection and preventing automatic start up.
- Burst resistant and tool-free safety guard for best user protection and fast adjustment.
- Multi position side handle for ease of use.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 BSX

- Voltage: 18 V
- No load stroke rate: 3000 spm
- Max. cutting depth in aluminium/metal pipe: 25 / 150 mm
- Max. cutting depth in non-ferrous metal/soft-wood/steel: 25 / 300 / 30 mm
- Vibration cutting wooden beam uncertainty: 1.5 m/s²
- Vibration cutting wooden beam: 15.2 m/s²
- Vibration sawing of wood uncertainty: 1.5 m/s²
- Vibration sawing of wood: 18 m/s²



- Stroke length: 28.6 mm
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 4 kg

- High performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Patented FIXTEC™ clamp for fast and easy keyless blade change.
- Counter balance mechanism to reduce vibrations 15.2 m/s² in wooden beams.
- 28.6 mm stroke length & 3000 strokes per minute for extremely fast cutting.
- Fuel gauge displays remaining charge.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 BIW12

- Voltage: 18 V
- Impact rate: 0 - 3350 ipm
- No load speed: 0 - 2450 rpm
- Max. torque: 240 Nm
- Tool reception: 1/2" square
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 1.9 kg

- Compact ½" impact wrench measures 155 mm in length making it ideal for working within confined spaces.
- High performance 4-pole motor delivers maximum power whilst maximising the power to weight ratio.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Heavy duty full metal gearbox and gears for superior durability and maximum torque.
- ½" square drive for use with universal sockets.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

• Supplied in bag with 2 batteries and charger.

FEATURES

Symbol	M18 CBLPP4B-502B
Opis	wiertarko-wkrętarka, klucz udarowy, szlifierka kątowa, piła, 2 akumulatory, ładowarka
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.0

