



SYMBOL: **4933464270** MANUFACTURER: **Milwaukee** EAN: **4058546222154**



M18 FPP2C2-502X - POWERPACK M18™ FUEL™, M18 FPD2, M18 FIWF12, 2 x 5.0 Ah + charger, in case, 4933464270

- Set contains:
 - M18 FPD2 - percussion drill 18 V
 - [M18 FIWF12](#) - 1/2" Impact wrench 300 Nm, 18 V
 - [M18 B5](#) - 2 batteries 5.0 Ah
 - [M12-18 FC](#) - charger 59 min
- Supplied in case (HD Box)



Product page

link > <https://imilwauke.pl/en/20554-m18-fpp2c2-502x-powerpack-m18-fuel-m18-fpd2-m18-fiwf12-2-x-50-ah-ch...>

DESCRIPTION

M18 FPD2

- Voltage: 18 V
 - Chuck capacity: 13 mm
 - Max. drilling masonry/steel/wood: 16/16/89 mm
 - Max. percussion rate: 0 - 32000 bpm
 - Max. torque: 135 Nm
 - No load speed gear 1/2: 0-550/0-2000 rpm
 - Speed settings: 2
 - Battery type: Li-ion
 - Weight with battery pack: 2.2 kg
-
- Higher power efficiency under load - outstanding torque of 135 Nm.
 - Extremely compact design of 175 mm length for access into tight spaces.
 - Advanced heavy duty chuck providing increased bit grip.
 - Brushless POWERSTATE™ motor for heavy application under load.
 - 13 mm metal chuck for quick bit changes and bit retention.
 - REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
 - Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
 - Battery fuel gauge displays remaining charge.
 - 40 percent brighter LED workspace illumination - vs previous model.
 - All metal reversible belt clip to hang your tool quickly and easily.
 - Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FIWF12

- Voltage: 18 V
 - Max. torque: 40/120/300/120 Nm
 - Impact rate: 2400/2600/3100/2600 ipm
 - No load speed: 1700/2000/2500/2000 rpm
 - Tool holder: 1/2" square
 - Battery type: Li-ion
 - Weight with battery pack: 1.8 kg
-
- Sound power level measured: 104.5 dB(A)
 - Sound pressure level: 93.5 dB(A)
 - Brushless POWERSTATE™ motor for longer motor life and up to 20% more power.
 - REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
 - 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
 - Mode 1 for precision work.
 - Mode 2 helps prevent damage to fasteners and material.
 - Mode 3 delivers maximum performance for the toughest applications.
 - Mode 4 intelligently detects when the tool has impacted on a fastener for one second automatically shutting the tool down, reducing overdriving and damaging materials.
 - 1/2" friction ring reception.
 - REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
 - Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
 - On board fuel gauge and LED light.
 - All metal reversible belt clip – quickly and easily hang tool.
 - Flexible battery system: works with all MILWAUKEE® M18™ batteries.

- Supplied in case (HD Box) with 2 batteries and charger.



FEATURES

Symbol	M18 FPP2C2-502X
Opis	wiertarko-wkrętarka udarowa, klucz udarowy, 2 akumulatory, ładowarka
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.0

