



SYMBOL: **4933464525** MANUFACTURER: **Milwaukee** EAN: **4058546224707**



M18 ONEDD2-0X - Drill driver 18 V, ONE-KEY™, in case, with 2 batteries and charger, 4933464525

- Voltage: 18 V
- No load speed gear 1/2: 0-550/0-2000 rpm
- Max. torque: 135 Nm
- Chuck capacity: 13 mm
- Speed settings: 2
- Max. drilling wood/ metal: 89/16 mm
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 5.0 Ah
- Charger supplied: 59 min
- Weight with battery pack: 2.1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page link > <https://imilwauke.pl/en/20567-m18-onedd2-0x-drill-driver-18-v-one-key-in-case-with-2-batteries-an...>

DESCRIPTION

- Higher power efficiency under load - outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
- ONE-KEY™ tool customisation allows the user to optimise their tool for a specific application.
- Customise anti-kickback control via ONE-KEY™ app.
- ONE-KEY™ tool tracking & security offers a Cloud-based inventory management platform that supports both location tracking and theft prevention.
- Save up to 4 custom settings to the tools memory for fast selection on the jobsite.
- Configure to any application choosing optimum tool settings for repeatable precision.
- Control speed, torque, start and end speeds, anti-kickback functions and LED.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#)
- Supplied in case (HD Box) with 2 batteries and charger.

FEATURES

| | |
|--------------------------------|----------------|
| Symbol | M18ONEDD2-502Z |
| Typ | bezударowa |
| Nm max | 135.00 |
| Ilość akumulatorów | 2 |
| Ilość biegów | 2 |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 18 |
| Średnica uchwytu wiertarskiego | 13.00 |
| Średnica wiercenia w drewnie | 89.00 |
| Średnica wiercenia w metalu | 16.00 |
| Obroty [obr/min] | 0-550/0-2000 |

