



SYMBOL: **4933464969** MANUFACTURER: **Milwaukee** EAN: **4058546229146**



M12 ONEFTR12-OC - 1/2" Digital torque wrench +/- 2%, 12 V, FUEL™, ONE-KEY™, in case, without equipment

- Voltage: 12 V
- Accuracy: CW ±2%, CCW ±3%
- Torque range: 16.9 - 203.4 Nm
- No load speed: 0-100 rpm
- Tool holder: 1/2" square
- Battery type: Li-ion
- No. of batteries supplied: 0
- Length: 586.7 mm
- Weight with battery pack: 2.6 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~4 059,00 zł~~ **-10%**

3 653,10 zł (tax excl.)

(4 493,31 zł (tax incl.))

PayU **VISA** **MasterCard**

Product page

link > <https://imilwauke.pl/en/20572-m12-oneftr12-oc-12-digital-torque-wrench-2-12-v-fuelone-key-in-case...>

DESCRIPTION

- Milwaukee Tool's first digital torque wrench, delivers up to 50% faster installation by replacing the hand tool.
- Provides 16.9 - 203.4 Nm of torque range and accuracy within ±2% for torque critical fasteners.
- Faster, more productive torque reporting with ONE-KEY™ providing torque data and customisable reports for inspectors or owners.
- Adjustable run-down torque to control the tools output torque via the motor to prevent over torque.
- Four measurement modes (ft-lb, in-lb, Nm, Kg-cm) and 15 available presets.
- Durable design to withstand the most demanding jobsite environments.
- Four notification modes that the tool is reaching, meeting or exceeding the torque target (audible, LED, LCD, and vibratory).
- Six pre-programmed languages including English, Spanish and French.
- Integrates three MILWAUKEE® exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™-ION battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite.
- Flexible battery system: works with all MILWAUKEE® M12™ [batteries](#).
- Supplied in case (Kitbox) without battery and charger.

FEATURES

Symbol	M12ONEFTR12-OC
L [mm]	586.70
Waga [kg]	2.42
Typ	ONE-KEY
Nm min	16.90
Nm max	203.40
Dokładność	±2%
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	12