



SYMBOL: **4933471406** MANUFACTURER: **Milwaukee** EAN: **4058546290344**



M18 FFN-OC - Framing nailer 18 V, FUEL™, in case, without equipment, 4933471406

- Voltage: 18 V
- Magazine angle: 30/34°
- Magazine capacity: 57
- Nail diameter: 2.9/3.32 mm
- Nail type: 50/90 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 5.1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



3 249,00 zł **-10%**

2 924,10 zł (tax excl.)

(3 596,64 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://imilwauke.pl/en/20578-m18-ffn-oc-framing-nailer-18-v-fuel-in-case-without-equipment-49334...>

DESCRIPTION

- Best-in-class power to consistently seat nails sub-flush to the surface in hardwoods.
- Ready to Fire Nail Technology eliminates ramp-up time between each nail discharge.
- No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance.
- Two mode selection allows for sequential fire for precision or bump fire for speed.
- Tool-free, quick and easy depth adjustment to assure nails are driven sub-flush.
- Dry-Fire lockout stops the tool being fired when there are no nails left in the magazine.
- Fires up to 700 nails per charge on a REDLITHIUM™-ION 5.0 Ah battery pack for maximum productivity.
- Fires standard framing nails which fits an angled magazine at 30° or 34°.
- Quick access and easy clearing of jams.
- LED work light illuminates the work surface for better placement of nails.
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™-ION battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite.
- Flexible battery system: works with all MILWAUKEE® M18™ [batteries](#).
- Supplied in case (Kitbox) without battery and charger.

FEATURES

Symbol	M18FFN-OC
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność magazynka	57.00
Średnica gwoździa	2.9/3.32