



SYMBOL: **4933471148** MANUFACTURER: **Milwaukee** EAN: **4058546287764**



M18 FPP4A-503P - POWERPACK M18™ FUEL™, M18 FPD2, M18 FIWF12, M18 CAG125XPDB, M18 CHX, 3 x 5.0 Ah + charger, in box, 4933471148

- Set contains:
 - M18 FPD2 - percussion drill 18 V
 - [M18 FIWF12](#) - 1/2" impact wrench, 300 Nm, 18 V
 - [M18 CAG125XPDB](#) - braking grinder 125 mm, 18 V, paddle switch
 - [M18 CHX](#) - SDS-Plus hammer 18 V
 - [M18 B5](#) - 3 batteries 5.0 Ah
 - [M12-18FC](#) - fast charger 59 min
- Supplied in packout trolley box



Product page

link > <https://imilwauke.pl/en/20611-m18-fpp4a-503p-powerpack-m18-fuel-m18-fpd2-m18-fiwf12-m18-cag125xpd...>



DESCRIPTION

M18 FPD2

- Voltage: 18 V
- Max. drilling masonry/steel/wood: 16/16/89 mm
- Max. percussion rate: 0 - 32000 bpm
- No load speed gear 1/2: 0-550/0-2000 rpm
- Max. torque: 135 Nm
- Speed settings: 2
- Chuck capacity: 13 mm
- Weight with battery pack: 2.2 kg
- Higher power efficiency under load - outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
- Brushless POWERSTATE™ motor for heavy application under load.
- 13 mm metal chuck for quick bit changes and bit retention.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Battery fuel gauge displays remaining charge.
- 40 percent brighter LED workspace illumination - vs previous model.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FIWF12

- Voltage: 18 V
- Max. torque: 40/120/300/120 Nm
- Impact rate: 2400/2600/3100/2600 ipm
- No load speed: 1700/2000/2500/2000 rpm
- Tool holder: 1/2" square
- Battery type: Li-ion
- Weight with battery pack: 1.8 kg
- Sound power level measured: 104.5 dB(A)
- Sound pressure level: 93.5 dB(A)
- Brushless POWERSTATE™ motor for longer motor life and up to 20% more power.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 1 for precision work.
- Mode 2 helps prevent damage to fasteners and material.
- Mode 3 delivers maximum performance for the toughest applications.
- Mode 4 intelligently detects when the tool has impacted on a fastener for one second automatically shutting the tool down, reducing overdriving and damaging materials.
- 1/2" friction ring reception.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light.
- All metal reversible belt clip – quickly and easily hang tool.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 CAG125XPDB

- Voltage: 18 V
- Disc diameter: 125 mm
- Max. cutting depth: 33 mm
- No load speed: 8500 rpm



- Braking time: < 2s
- Spindle size: M14
- Paddle switch
- Brake: yes
- FIXTEC: yes
- Line lock out function: yes
- Anti-kickback protection: yes
- Battery type: Li-ion
- Weight with battery pack: 2.7 kg

- Vibration sanding: 2.15 m/s²
- Vibration at grinding metal: 4.61 m/s²
- Sound power level measured: 89.9 dB(A)
- Sound pressure level: 78.9 dB(A)
- Brushless POWERSTATE™ motor with the power to grind and up to 10x more tool life.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- RAPIDSTOP™ for fastest disc brake in less than 2 seconds and best user protection.
- Safety paddle switch with line-lock-out function to prevent automatic start up.
- Premium gearing system - same system as used at high performance corded grinders.
- Slim handle design with paddle switch.
- Removable dust screen to prevent debris entrance, prolonging motor life.
- 125 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner.
- FIXTEC™ nut for tool-free disc change.
- Anti-vibration side handle for lower vibration.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Standard equipment: quick release safety guard, AVS side handle, flange, FIXTEC nut, 2x dust screens.

M18 CHX

- Voltage: 18 V
- Max. drilling wood/steel/concrete: 30/13/26 mm
- Max. percussion rate: 0 - 5100 bpm
- No load speed: 0 - 1400 rpm
- Optimised drilling capacity in concrete: 6 - 20 mm
- Vibration chiseling: 9.5 m/s²
- Vibration chiselling uncertainty: 1.5 m/s²
- Vibration drilling: 8.9 m/s²
- Battery type: Li-ion
- Weight with battery pack: 3.5 kg

- Brushless POWERSTATE™ motor for up to 2x longer motor life and up to 25% more power.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Second hardest hitting SDS hammer in its class. Powerful hammer mechanism delivers 2.5 J of impact energy at low 8.9 m/s² vibrations.
- Compact, ergonomic design for increased end user comfort.
- All metal gear case - optimum seating of the gears for enhanced service life.
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility.
- FIXTEC™ system - keyless chuck changing.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Compatible with M18 CDEX dust extractor.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

- Supplied in Packout with 3 batteries and charger.

FEATURES

Symbol	M18FPP4A-503P
Opis	wiertarko-wkrętarz, klucz udarowy, szlifierka kątowna, młot, 3 akumulatory, ładowarka
Ilość akumulatorów	3
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.0