





SYMBOL: 4933471148

MANUFACTURER: Milwaukee EAN: 4058546287764

M18 FPP4A-503P - POWERPACK M18™ FUEL™, M18 FPD2, M18 FIWF12, M18 CAG125XPDB, M18 CHX, 3 x 5.0 Ah + charger, in box

- · Set contains:
- M18 FPD2 percussion drill 18 V
- M18 FIWF12 1/2" impact wrench, 300 Nm, 18 V
- M18 CAG125XPDB braking grinder 125 mm, 18 V, paddle switch
- M18 CHX SDS-Plus hammer 18 V
- M18 B5 3 batteries 5.0 Ah
- M12-18FC- fast charger 59 min
- · Supplied in packout trolley box



link > https://imilwauke.pl/en/20611-m18-fpp4a-503p-powerpack-m18-fuel-m18-fpd2-m18-fiwf12-m18-cag125xpd.



DESCRIPTION

M18 FPD2

- · Voltage: 18 V Max. drilling masonry/steel/wood: 16/16/89 mm
- · Max. percussion rate: 0 32000 bpm
- No load speed gear 1/2: 0-550/0-2000 rpm
- Max. torque: 135 Nm
- Chuck capacity: 13 mm
- · Weight with battery pack: 2.2 kg
- · Higher power efficiency under load outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
 Advanced heavy duty chuck providing increased bit grip.
- Brushless POWERSTATE $^{\text{m}}$ motor for heavy application under load.
- 13 mm metal chuck for quick bit changes and bit retention.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life. Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Battery fuel gauge displays remaining charge.
- 40 percent brighter LED workspace illumination vs previous model
- · All metal reversible belt clip to hang your tool quickly and easily.
- · Flexible battery system: works with all MILWAUKEE® M18™ batteries

M18 FIWF12

- Max. torque: 40/120/300/120 Nm • Impact rate: 2400/2600/3100/2600 ipm
- No load speed: 1700/2000/2500/2000 rpm
- Tool holder: 1/2" square · Battery type: Li-ion
- · Weight with battery pack: 1.8 kg
- Sound power level measured: 104.5 dB(A)
- Brushless POWERSTATE™ motor for longer motor life and up to 20% more power
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- · Mode 1 for precision work.
- Mode 2 helps prevent damage to fasteners and material.
- Mode 3 delivers maximum performance for the toughest applications
- Mode 4 intelligently detects when the tool has impacted on a fastener for one second automatically shutting the tool down, reducing overdriving and damaging materials. 1/2" friction ring reception.

 REDLITHIUM"*ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- · Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- · On board fuel gauge and LED light.
- · All metal reversible belt clip quickly and easily hang tool.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 CAG125XPDB

- Disc diameter: 125 mm
- Max. cutting depth: 33 mm
- · No load speed: 8500 rpm



- Braking time: < 2s
- Spindle size: M14
- · Paddle switch
- Brake: yes
- FIXTEC: yes
- · Line lock out function: yes
- Anti-kickback protection: yes
- · Battery type: Li-ion
- Weight with battery pack: 2.7 kg
- Vibration sanding: 2.15 m/s²
 Vibration at grinding metal: 4.61 m/s²
- Sound power level measured: 89.9 dB(A) Sound pressure level: 78.9 dB(A)

- Brushless POWERSTATE™ motor with the power to grind and up to 10x more tool life.
 REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- RAPIDSTOP™ for fastest disc brake in less than 2 seconds and best user protection.
- Safety paddle switch with line-lock-out function to prevent automatic start up.
- Premium gearing system same system as used at high performance corded grinders.
 Slim handle design with paddle switch.

- Removable dust screen to prevent debris entrance, prolonging motor life.

 125 mm keyless guard great cutting capacity and fast guard adjustment without using a spanner.
- FIXTEC™ nut for tool-free disc change.
 Anti-vibration side handle for lower vibration.
- $\cdot \text{Individual battery cell monitoring optimises tool run time and ensures long term pack durability}. \\$
- · Fuel gauge displays remaining charge.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- $\bullet \, \text{Standard equipment: quick release safety guard, AVS side handle, flange, FIXTEC \, nut, 2x \, dust \, screens. } \\$

- Voltage: 18 V
 Max. drilling wood/steel/concrete: 30/13/26 mm
- Max. percussion rate: 0 5100 bpm
- No load speed: 0 1400 rpm
- Optimised drilling capacity in concrete: 6 20 mm
- Vibration chiseling: 9.5 m/s²
 Vibration chiselling uncertainty: 1.5 m/s²
- Vibration drilling: 8.9 m/s²
- · Battery type: Li-ion
- Weight with battery pack: 3.5 kg
- Brushless POWERSTATE™ motor for up to 2x longer motor life and up to 25% more power.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM** battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
 Second hardest hitting SDS hammer in its class. Powerful hammer mechanism delivers 2.5 J of impact energy at low 8.9 m/s² vibrations.

- Compact, ergonomic design for increased end user comfort.
 All metal gear case optimum seating of the gears for enhanced service life.
- $\bullet \text{ 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility. } \\$
- . FIXTEC™ system keyless chuck changing.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- · Fuel gauge displays remaining charge.
- · Compatible with M18 CDEX dust extractor • Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Supplied in Packout with 3 batteries and charger.

FEATURES

Symbol	M18FPP4A-503P
Opis	wiertarko-wkrętarka, klucz udarowy, szlifierka kątowa, młot, 3 akumulatory, ładowarka
Ilość akumulatorów	3
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.0



