



SYMBOL: **4933478498** MANUFACTURER: **Milwaukee** EAN: **4058546346911**



M18 ONEFHPXDEL-552C - High performance SDS-Plus hammer with dedicated dust extractor 18 V, FUEL™, ONE-KEY™, 2 x 5.5 Ah + charger

- Set includes:
 - M18 ONEFHPX - M18 FUEL™ high performance 4-mode 32 mm SDSPlus hammer with ONE-KEY™ and FIXTEC™ chuck.
 - M18 FPDDEXL - Dedicated dust extraction for M18 FUEL™ 32 mm SDS-Plus hammers with AUTOPULSE™.
 - M18 HB5.5 - 2 x 5.5 Ah
 - M12-18 FC - charger
 - Supplied in case (Kitbox).

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~5 399,00 zł~~ **-10%**

4 859,10 zł (tax excl.)

(5 976,69 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://imilwauke.pl/en/22089-m18-onefhpixel-552c-high-performance-sds-plus-hammer-with-dedicated...>

DESCRIPTION

M18 ONEFHPX

- Voltage: 18 V
- Blow energy: 5.0 J
- Max. percussion rate: 0-4600 bpm
- No load speed: 0-800 rpm
- Max. drilling wood/steel/concrete: 30/13/32 mm
- Vibration drilling: 6.9 m/s²
- Vibration chiseling: 7.4 m/s²
- Battery type: Li-ion
- Weight with battery pack (M18 HB5.5): 5.2 kg

- Hardest hitting cordless SDS-Plus hammer in its class. Powerful hammer mechanism delivers 5.0 J (EPTA) of impact energy at low 6.9 m/s² vibrations.
- Drills up to 10 Ø18 x 100 mm holes on a M18™ HIGH OUTPUT™ 5.5 Ah battery charge.
- AUTOSTOP™ shuts down the tool to protect the user of sharp movement in bind up situations.
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools.
- ONE-KEY™ also features a remote locking functionality.
- FIXTEC™ system for keyless chuck changing between SDS-Plus and 13 mm metal chuck.
- All metal gear case - optimum seating of the gears for enhanced tool life.
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility.
- Compatible with M18 FPDDEXL dust extractor.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE's POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.

M18 FPDDEXL

- Voltage: 18 V
- Max. drill bit diameter: 32 mm
- Max. drilling depth: 230 mm
- Max. drill bit length: 260 mm
- Stroke length: 203 mm
- Battery type: Li-ion
- Weight: 2 kg

- Designed to collect dust efficiently with automatic operation from the tools on/ off trigger switch.
- AUTOPULSE™ industry's first on-board automatic filter cleaning mechanism for an on-tool dust extractor, which increases the air flow efficiency as well as the filter life time.
- The highly efficient HEPA filter collects 99.97 % of airborne particles down to 0.3 microns.
- Translucent dust box allows user to see the current level of dust inside as well as when the dust box is full.
- Dust box with vacuum port allows user to attach to large dust extractors to suction out dust from the box.
- Optimised to be used with AS 30 LAC 30 I dust extractor and DEK26 hose clip adapter (4931447295).
- Exchangeable nozzles to adjust to the different drilling diameters.
- Supplied with 2 nozzle sizes 1x up to Ø16 mm, 1x up to Ø32 mm, which can be quickly switched thanks to the quick lock mechanism.
- Dust extraction aluminium tube is adjustable according to the size of the drill bit and length up to 230 mm depth.
- Adjustable depth gauge with easily and precisely adjustment buttons for accurate hole depths.
- Removable and switchable depth gauge, in case the user prefers the other side.

- Supplied in case (Kitbox) with 2 batteries and charger.

FEATURES

Symbol	M18ONEFHPXDEL-552C
--------	--------------------

Waga [kg]	7.20
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-4600
Energia uderu	5.00
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	32.00
Średnica wiercenia w drewnie	30.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-800

