





SYMBOL: 4933478503

MANUFACTURER: Milwaukee

FAN: 4058546346966

M18 ONEFHX-0X - 4-mode 26 mm SDS-Plus hammer FUEL™, ONE-KEY™ 18 V, in case, without equipment, 4933478503

- · Voltage: 18 V
- · Blow energy: 2.5 J
- Max. percussion rate: 0-4800 bpm
- No load speed: 0-1330 rpm
- Max. drilling wood/steel/concrete: 28/13/26 mm
- Optimised drilling capacity in concrete: 6-20 mm
- Vibration drilling: 12.9 m/s²
- Vibration chiseling: 14.2 m/s²
- Tool reception: SDS-Plus + Reduced shank 13 mm
- Battery type: Li-ion
- Weight with battery pack (M18 HB5.5): 4.5 kg
- · Weight: 3.4 kg

■ WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)













2 087,10 zł (tax excl.)

(2 567,13 zł (tax incl.))



link > https://imilwauke.pl/en/22091-m18-onefhx-0x-4-mode-26-mm-sds-plus-hammer-fuel-one-key-18-v-in-cas...

DESCRIPTION

- The fastest drilling rotary hammer in its class leading to increased productivity.
- Powerful hammer mechanism delivers 2.5 J of impact energy at low 12.9 m/s² vibrations.
 Drills up to 125 №10 x 50 mm holes on a M18™ HIGH OUTPUT™ 5.5 Ah battery charge.
- AUTOSTOP™ shuts down the tool to protect the user of sharp movement in bind up situations.
 ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools.
- ONE-KEY™ also features a remote locking functionality
- FIXTEC™ system for keyless chuck changing between SDS-Plus and 13 mm metal chuck.
- · All metal gear case optimum seating of the gears for enhanced tool life.
- · 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility.
- Compatible with M18 FCDDEXL or M18 FDDEXL dust extractors.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time. These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries.

• Supplied in case (HD Box) without battery and charger.

FEATURES

Symbol	M180NEFHX-0X
Waga [kg]	4.50
Uchwyt	SDS-Plus
Częstość udaru [ud/min]	0-4800
Energia udaru	2.50
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	26.00
Średnica wiercenia w drewnie	28.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1330