



SYMBOL: **4933441260** MANUFACTURER: **Milwaukee** EAN: **4002395001330**



## HD18 HIW-402C - Impact wrench with pin detent 1/2", 610 Nm, 18 V, in case, with 2 batteries and charger, 4933441260

- Voltage: 18 V
- Impact rate: 0 - 2200 ipm
- Max. torque: 610 Nm
- No load speed: 0 - 1900 rpm
- Tool reception: 1/2" square
- Battery type: Li-ion
- Weight with battery pack: 3 kg



Product page

link > <https://imilwauke.pl/en/22101-hd18-hiw-402c-impact-wrench-with-pin-detent-12-610-nm-18-v-in-case-...>



### DESCRIPTION

- Engineered for heavy use, the M18™ impact wrench delivers maximum cordless power on the jobsite.
- With its Milwaukee® 4-pole frameless motor it delivers a staggering 610 Nm of torque, ideal for powering through the toughest of applications.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- 1/2" square drive with detent pin for secure socket retention.
- Ideal for heavy applications such as steel fabrication, mechanical fastening, industrial construction and automotive work.
- Light weight and ergonomically designed.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all Milwaukee® M18™ batteries.
- Supplied in case (Kitbox) with 2 batteries and charger.

### FEATURES

|                          |              |
|--------------------------|--------------|
| Symbol                   | HD18HIW-402C |
| Wyjście                  | 1/2"         |
| Nm max                   | 610          |
| Częstość uderu [ud/min]  | 0-2200       |
| Ilość akumulatorów       | 2            |
| Zasilanie                | battery      |
| Napięcie akumulatora [V] | 18           |
| Obroty [obr/min]         | 0-1900       |

