



SYMBOL: **4933478444** MANUFACTURER: **Milwaukee** EAN: **4058546346355**



M18 FIW2F12-502X - Compact impact wrench with friction ring 1/2", 339 Nm, 18 V, 5.0 Ah, in case, with 2 batteries and charger

- Voltage: 18 V
- Max. fastening torque: 339 Nm
- Nut-busting torque: 339 Nm
- Impact rate: 0-1000/0-2400/0-3500 ipm
- Max. torque: 102/203/339/34 Nm
- No load speed: 0-900/0-1650/0-2400/0-1200 rpm
- Tool reception: 1/2" square
- Battery type: Li-ion
- Weight with battery pack: 1.8 kg



~~2 869,00 zł~~ **-10%**

2 582,10 zł (tax excl.)

(3 175,98 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://imilwauke.pl/en/22112-m18-fiw2f12-502x-compact-impact-wrench-with-friction-ring-12-339-nm...>

DESCRIPTION

- Power efficiency under load - outstanding torque of 339 Nm.
- Extremely compact design - total length of just 124 mm for access into tight spaces.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops.
- Auto shut-off control applies no more than 34 Nm of torque for hand-tight fastening applications to prevent over tightening.
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- 1/2" square friction ring.
- Reversible belt hook.
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Supplied In case (HD Box) with 2 batteries and charger.

FEATURES

Symbol	M18FIW2F12-502X
Wyjście	1/2"
Nm max	339
Częstość uderu [ud/min]	1000/2400/3500
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	900/1650/2400/1200