



SYMBOL: **4933478452** MANUFACTURER: **Milwaukee** EAN: **4058546346430**



## M18 FMTIW2P12-0X - Impact wrench with pin detent 1/2", 745 Nm, 18 V, FUEL™, in case, without batteries and charger

- Voltage: 18 V
- Impact rate: 0-900/0-2100/0-3100 ipm
- No load speed: 0-1250/0-1950/0-2575/0-1325 rpm
- Max. torque: 475/610/745/47 Nm
- Max. bolt diameter: M22
- Max. fastening torque: 745 Nm
- Nut-busting torque: 881 Nm
- Tool reception: 1/2" square
- Battery type: Li-ion
- Weight with battery pack: 2.3 kg



~~1 899,00 zł~~ **-10%**

**1 709,10 zł** (tax excl.)

(2 102,19 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://imilwauke.pl/en/22117-m18-fmtiw2p12-0x-impact-wrench-with-pin-detent-12-745-nm-18-v-fuel-...>

### DESCRIPTION

- Most versatile cordless impact wrench in the MILWAUKEE® impressive arsenal with an industry-leading performance at 881 Nm of nut-busting torque and 745 Nm of fastening torque.
- Incredibly compact design for this performance level, with only 152 mm overall length ideal for applications in tight spaces.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops.
- Auto shut-off control applies no more than 47 Nm of torque for hand-tight fastening applications to prevent over-tightening.
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- 1/2" square detent pin.
- Reversible belt hook.
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Supplied in case (HD Box) without batteries and charger.

### FEATURES

Symbol	M18FMTIW2P12-0X
Wyjście	1/2"
Nm max	745
Częstość uderu [ud/min]	900/2100/3100
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	1250/1950/2575/1325