



SYMBOL: **4933478650** MANUFACTURER: **Milwaukee** EAN: **4058546348434**



## M18 FIW2F38-0X - Compact impact wrench with friction ring 3/8", 339 Nm, 18 V, FUEL™, in case, without batteries and charger

- Voltage: 18 V
- Impact rate: 0-1000/0-2400/0-3500 ipm
- No load speed: 0-800/0-1650/0-2400/0-1000 rpm
- Max. torque: 102/203/339/34 Nm
- Max. fastening torque: 339 Nm
- Nut-busting torque: 339 Nm
- Tool reception: 3/8" square
- Battery type: Li-ion
- Weight with battery pack: 1.8 kg



1 549,00 zł **-10%**

**1 394,10 zł** (tax excl.)

(1 714,74 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://imilwauke.pl/en/22119-m18-fiw2f38-0x-compact-impact-wrench-with-friction-ring-38-339-nm-1...>

### DESCRIPTION

- The most compact cordless impact wrench in its class, delivering the most access in tight spaces, with performance at 339 Nm of fastening torque.
- Incredibly compact design for this performance level, with only 124 mm overall length ideal for applications in tight spaces.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops.
- Auto shut-off control applies no more than 34 Nm of torque for hand-tight fastening applications to prevent over tightening.
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- 3/8" square friction ring.
- Reversible belt hook.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- **Supplied In case (HD Box) without batteries and charger.**

### FEATURES

Symbol	M18FIW2F38-0X
Wyjście	3/8"
Nm max	339
Częstość uderu [ud/min]	1000/2400/3500
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	800/1650/2400/1000

