



SYMBOL: **4933478435** MANUFACTURER: **Milwaukee** EAN: **4058546346263**



M18 ONEFSAG125XPDB-502X - Angle grinder diam. 125 mm, 18 V, in case with 2 batteries and charger, 4933478435

- Voltage: 18 V
- Battery type: Li-ion
- Braking time: <2 s
- Switch lock function: Yes
- Soft start function: Yes
- Brake: Yes
- Spindle thread: M14
- Maximum cutting depth: 33 mm
- Dial diameter: 125 mm
- Switch type: paddle switch
- No load speed: 8500 rpm
- Weight with battery (M18 B5): 2,7 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~3 299,00 zł~~ **-10%**

2 969,10 zł (tax excl.)

(3 651,99 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://imilwauke.pl/en/22130-m18-onefsag125xpdb-502x-angle-grinder-diam-125-mm-18-v-in-case-with...>

DESCRIPTION

- Smaller head and angle for the battery - for better balance and ergonomics compared to the previous model.
- Removable dust screen to prevent ingress of dirt. This extends the life of the engine.
- Provides the same performance as a corded 1200 W grinder.
- 125 mm guard for greater cutting depth and quick adjustment of the guard without a key.
- Featuring three exclusive integrated MILWAUKEE technologies - the POWERSTATE brushless motor, the REDLITHIUM battery pack and the REDLINK PLUS intelligence hardware and software - delivering outstanding power, long run time and durability.
- Flexible battery system: works with all MILWAUKEE M18 batteries.
- ONE-KEY Locking, Tracking & Tool Security provides a cloud-based inventory management platform that supports both location tracking and theft prevention.
- RAPIDSTOP disc brake brakes the disc within 2 seconds for improved user protection.
- Non-lockable safety switch with line-lock-out function to prevent automatic start-up.
- Side lever with anti-vibration for less vibration.
- Integrated FIXTEC system for disc change without tools.
- Slim handle design.
- Supplied in case (HD Box) with 2 batteries and charger.

FEATURES

| | |
|--------------------------|------------------------|
| Symbol | M18ONEFSAG125XPDB-502X |
| Ilość akumulatorów | 2 |
| Zasilanie | battery |
| Napięcie akumulatora [V] | 18 |
| Średnica tarczy | 125.00 |
| Typ włącznika | łopatkowy |
| Obroty [obr/min] | 8500 |