



SYMBOL: **4933478437** MANUFACTURER: **Milwaukee promo** EAN: **4058546346287**



M18 FSAGV125XPDB-0X - Angle grinder 125 mm, 18 V, in case without equipment, 4933478437

- Voltage: 18 V
- Disc diameter: 125 mm
- Max. cutting depth: 33 mm
- No load speed: 3500 - 8500 rpm
- Spindle size: M14
- Switch type: Paddle (Deadman) switch
- Brake: Yes
- Braking time: < 2s
- Line lock out function: Yes
- Soft start function: Yes
- Anti-kickback protection: Yes
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2,7 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~1 899,00 zł~~ **-20%**

1 528,55 zł (tax excl.)

(1 880,12 zł (tax incl.))

PayU VISA MasterCard

Product page

link > <https://imilwauke.pl/en/22132-m18-fsagv125xpdb-0x-angle-grinder-125-mm-18-v-in-case-without-equip...>

DESCRIPTION

- Maximum control for every application - 5-step speed dial ideal for working with stainless steel and aluminum & for rust and paint removal.
- Delivering corded performance similar to a 1200 W grinder.
- RAPIDSTOP™ for fastest disc brake in less than 2 seconds and best user protection.
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up.
- Anti-vibration side handle for lower vibration.
- Integrated FIXTEC™ system for tool-free wheel change.
- Slim handle design.
- Removable dust screen to prevent debris entrance, prolonging motor life.
- 125 mm keyless guard for great cutting capacity and fast guard adjustment without using a key.
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Supplied in case (HD Box) without battery and charger.

FEATURES

Symbol	M18FSAGV125XPDB-0X
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica tarczy	125.00
Typ włącznika	łopatkowy
Obroty [obr/min]	3500-8500