



SYMBOL: **4933464831** MANUFACTURER: **Milwaukee** EAN: **4058546227760**



## M18 FHPP3A-122B - Set POWERPACK M18™, M18 FLAG230XPDB, M18 FSX, M18 FCS66, 2 x 12.0 Ah + charger, in the bag, 4933464831

• The kit includes: M18 FLAG230XPDB, M18 FSX, M18 FCS66, 2 x battery 12.0 Ah + charger, the bag.



Product page

link > <https://imilwauke.pl/en/22178-m18-fhpp3a-122b-set-powerpack-m18-m18-flag230pdb-m18-fsx-m18-fcs66...>



### DESCRIPTION

#### M18 FLAG230XPDB

- Voltage: 18 V.
- Battery type: Li-ion.
- Brake: Yes.
- Cutting depth: 65 mm.
- Disc diameter: 230 mm.
- Line lock out function: Yes.
- No load speed: 6600 rpm.
- Spindle size: M14.
- The world's first single 18V battery operated large angle grinder that delivers the power to grind, lighter than corded tools and makes up to 68 cuts per charge in 42 mm stainless steel pipe.
- Next generation POWERSTATE™ brushless motor, REDLINK PLUS™ electronics and REDLITHIUM™ HIGH OUTPUT™ 12.0 Ah battery pack deliver superior performance, durability and run time in high demand applications.
- Disc brake slows the disc down faster for improved user protection.
- Non-lockable safety paddle switch with line-lock-out function to prevent automatic start up.
- Keyless guard for great cutting capacity and fast guard adjustment without using a key.
- FIXTEC™ nut for tool-free disc change.
- Anti-vibration side handle for lower vibration.
- Removable dust screen to prevent debris entrance, prolonging motor life.

#### M18 FSX

- Voltage: 18 V.
- Battery type: Li-ion.
- Max. cutting depth in aluminium: 25 mm.
- Max. cutting depth in metal pipe: 150 mm.
- Max. cutting depth in non\_ferrous metal: 25 mm.
- Max. cutting depth in soft\_wood: 300 mm.
- Max. cutting depth in steel: 20 mm.
- No load stroke rate: 0-3000 spm.
- Stroke length: 32 mm.
- The M18 FUEL™ Super SAWZALL™ delivers the power to cut at the same speed as an equivalent AC reciprocating saw - with the ability to cut 150 pieces of 290 mm x 45 mm pine on one 12.0 Ah battery charge.
- Next generation POWERSTATE™ brushless motor, REDLINK PLUS™ electronics and REDLITHIUM™ HIGH OUTPUT™ 12.0 Ah battery pack deliver superior performance, durability and run time in high demand applications.
- Orbital action allows the saw to clear the cut of debris giving a faster cut in wood materials.
- 3000 SPM with a 32 mm stroke length delivers fast and effortless cutting in a wide range of materials.
- 5 variable speed settings from 1500 SPM to 3000 SPM to allow the correct speed to be set for the material being cut.
- FIXTEC™ blade clamp for fast and easy blade changes without any key.
- Durable metal rafter hang hook for work space management and safety.
- Adjustable shoe for optimised use of blades.
- Integrated LED light for workspace illumination.

#### M18 FCS66

- Voltage: 18 V.
- Battery type: Li-ion.
- Blade diameter: 190 mm.
- Bore size: 30 mm.
- Max. cutting depth 45°: 48 mm.
- Max. cutting depth 90°: 66 mm.
- No load speed: 5800 rpm.
- The M18 FUEL™ circular saw delivers the power to rip cut at the same feed rate of an equivalent AC circular saw - with the ability to cut 750 pieces of 90 mm x 45 mm pine stud on one 12.0 Ah battery charge.
- Next generation POWERSTATE™ brushless motor, REDLINK PLUS™ electronics and REDLITHIUM™ HIGH OUTPUT™ 12.0 Ah battery pack deliver superior performance, durability and run time in high demand applications.
- 190 mm blade which gives a 66 mm depth of cut, enabling the saw to cut 3 stacked OSB boards.
- Durable metal rafter hang hook for work space management and safety.
- Vacuum adaptor supplied fits directly to all MILWAUKEE® dust extractors.



- Magnesium shoe reduces weight and maximises durability.
- Integrated LED light for workspace illumination.
- 56° bevel capacity.

• Supplied in the bag with 2 battery and charger.

#### FEATURES

Symbol	M18FHPP3A-122B
Opis	szlifierka kąтова, piła, pilarka, 2 akumulatory, ładowarka
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	12.0

