



> Accessories > Drilling > Concrete drill bits > SDS-Plus



SYMBOL: **4932307082** 

MANUFACTURER: Milwaukee

FAN: 4002395308989

\*\*\*\*

4932307082 - Concrete impact drill bit SDS-Plus M2, 2-cut, 16 x 400/450 mm (1 pcs.)

- Diameter: 16 mm
- Total length: 450 mm
- Working length: 400 mm
- Pack quantity: 1



89,78 zł -10%

**80,80 zł** (tax excl.)

(99,38 zł (tax incl.))



Pay**U** VISA MasterCard

link > https://imilwauke.pl/en/22562-4932307082-concrete-impact-drill-bit-sds-plus-m2-2-cut-16-x-400450-link > https://imilwauke.pl/en/22562-493230-link > https://imilwauke.pl/en/2



## DESCRIPTION

- Breaker Points. 3 offset aggressive power breakers.
   These produce a "Demolition" effect and create micro cracks in the drilled material. Up to 25% FASTER.
- Centering tip. Ensures immediate spot drilling with pin point accuracy. Prevents skidding on smooth surfaces.
- · Enlarged rebar chamfers. Prevents side tip damage when hitting rebar
- Reduces the risk of the drill bit jamming when hitting rebar.
- Tapered shoulder design. Thinner shoulder towards drill tip for less friction providing for greater speed.
  Ideal for cordless hammers identified from its tapered shoulder geometry.
- Reinforced flute. High volume flute geometry for optimum dust removal.
- · Reinforced flute design (thicker core) gives:
- Full power transfer to the tip,
- Lower vibrations.
- Exceptional break resistance, less breakages and best durability.
- FASTEST: New aggressive tip geometry with 3 chip breakers demolishes the concrete quicker and a tapered shoulder design minimises friction enabling the M2 drill bit to deliver faster drilling speed.
- DURABILITY: Rebar chamfers on the tip prevent side tip damage when hitting metal reinforcement and a thicker core body ensures higher power transfer, lower vibrations and less flute breakages

## FEATURES

Symbol	4932307082
L [mm]	450.00
D	16.00
Тур	2-ostrzowe
Ilość elementów	1
Długość robocza	400.00
Uchwyt	SDS-Plus