



> Accessories > Drilling > Concrete drill bits > SDS-Max

SYMBOL: **4932352782** 

MANUFACTURER: Milwaukee EAN: 4002395374403

\*\*\*\*

4932352782 - Drill bit for concrete SDS-Max MX4, 4 cut, 28 x 1200/1320 mm

- Diameter: 28 mm
- Total length: 1320 mm
- Working length: 1200 mm
- Pack quantity: 1



906,98 zł -10%

**816,28** zł (tax excl.) (1 004,02 zł (tax incl.))



Pay**U** VISA MasterCard

link > https://imilwauke.pl/en/23371-4932352782-drill-bit-for-concrete-sds-max-mx4-4-cut-28-x-12001320-m...



## DESCRIPTION

- · Large carbide tip with patented rebar chamfers
- Ensures lower vibration and optimised drilling performance when hitting reinforced steel equalling longer life time.
- Especially developed robust head geometry with optimum 4 x 90° symmetry of carbide tip. Reduces jamming up on hitting reinforcing steel.
- Centering point with 130° point angle. Easy spot drilling with pinpoint accuracy and ensures optimum guidance during drilling.
   Big, robust secondary cutter with dynamic, curved cutting edge. Supports the primary cutter for faster drilling.
- Shorter spiral windings. For faster transport of drilling dust from the head to the flute = Less wear and heat build up at the tip.
   Innovative, unique carbide tip. With more carbide on all diameters and extra carbide on Ø > 32 mm.
- · Wear mark on both sides of primary cutter. Guarantees diameter accuracy i.e. for anchor fittings.
- Patented reinforced flute geometry. Lower vibrations for smoother drilling. Stronger flute means less breakages.
- Better transfer of hammer energy to the tip.
  Deep flute shoulders. High volume dust removal for optimum drilling speed less wear and heat build up.
- Low vibration drilling performance. Comfortable drilling ensures less stress for man and machine.
   Special surface treatment. Shot blasting provides a smooth surface and densifies the surface structure and makes the bit more wear resistant.
- PGM conformity. Guarantees precise holes for anchor fitting over the entire life time of the drill bit.

## FEATURES

Symbol	4932352782
L [mm]	1320.00
D	28.00
Тур	4-ostrzowe
Ilość elementów	1
Długość robocza	1200.00
Uchwyt	SDS-Max