



SYMBOL: **4933479153** MANUFACTURER: **Milwaukee** EAN: **4058546369477**



M18 FMTIW2F38-0X - 3/8" Mid Torque Impact wrench with friction ring, 745 Nm, 18 V, FUEL™, in case, without equipment

- Voltage: 18 V
- Max. bolt diameter: M22
- Impact rate: 0-900/0-2100/0-3100 ipm
- Max. torque: 475/610/745/47 Nm
- No load speed: 0-1200/0-1950/0-2575/0-1325 rpm
- Nut-busting torque: 813 Nm
- Max. fastening torque: 745 Nm
- Tool reception: 3/8" square
- Battery type: Li-ion
- Weight with battery pack: 2.3 kg



~~1 809,00 zł~~ **-10%**

1 628,10 zł (tax excl.)

(2 002,56 zł (tax incl.))



Product page

link > <https://imilwauke.pl/en/24929-m18-fmtiw2f38-0x-38-mid-torque-impact-wrench-with-friction-ring-745...>

DESCRIPTION

- Most versatile cordless impact wrench in the MILWAUKEE® impressive arsenal with an industry-leading performance at 813 Nm of nut-busting torque and 745 Nm of fastening torque.
- Incredibly compact design for this performance level, with only 152 mm overall length ideal for applications in tight spaces.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops.
- Auto shut-off control applies no more than 47 Nm of torque for hand-tight fastening applications to prevent over-tightening.
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- 3/8" square friction ring.
- Reversible belt hook.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Supplied in case (HD Box) without battery and charger.

FEATURES

Symbol	M18 FMTIW2F38-0X
Wyjście	3/8"
Nm max	475/610/745/47
Częstość uderu [ud/min]	900/2100/3100
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Obroty [obr/min]	1250/1950/2575/1325

