

SYMBOL: **4933478527** MANUFACTURER: **Milwaukee** EAN: **4058546347208**



## M12 FCOT-423X - Sub compact angle grinder 76 mm 12 V, FUEL™, in case, with 3 batteries and charger, 4933478527

- Voltage: 12 V
- Disc diameter: 76 mm
- Max. cutting depth: 16.3 mm
- No load speed: 20000 rpm
- Bore size: 10 mm
- Anti-kickback protection: No
- No. of batteries supplied: 3
- Battery pack capacity: 2 x 4.0 Ah, 1 x 2.0 Ah
- Battery type: Li-ion
- Weight with battery pack: 1.1 kg



Product page

link > <https://imilwauke.pl/en/25002-m12-fcot-423x-sub-compact-angle-grinder-76-mm-12-v-fuel-in-case-wit...>



### DESCRIPTION

- Fast accurate cutting with up to 20 000 RPM.
- Optimised ergonomic design for easy control and one-handed use. Only 1.1 kg and 226 mm in length.
- Multi-material cutting capability with variety of blades available (metal cut-off wheel, carbide abrasive blade and diamond tile blade).
- A very capable problem solving tool for cutting steel, stainless steel, non-ferrous materials, drywall, fibre cement, plastic and ceramics.
- Easily adjustable guard and unique forward/reverse selectable blade rotation direction to protect user from debris in various cutting positions.
- Quick release dust shoe with depth adjustment and optional dust extraction port.
- On board fuel gauge and LED light.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.
- 76 mm blade offers up to 16.3 mm depth of cut.
- Standard equipment: diamond tile blade, carbide abrasive blade, metal cut-off wheel, adjustable dust shoe.
- **Supplied in case (HD Box) with 3 batteries and charger.**

### FEATURES

Symbol	M12FCOT-423X
Ilość akumulatorów	3
Zasilanie	battery
Napięcie akumulatora [V]	12
Średnica tarczy	76.00
Typ włącznika	łopatkowy
Obrotы [obr/min]	20000