



SYMBOL: **4933478993** MANUFACTURER: **Milwaukee** EAN: **4058546362751**



## M18 FFN21-0C - Framing nailer 18 V, FUEL™, in case, without equipment, 4933478993

- Voltage: 18 V
- Collation angle: 20 - 22°
- Magazine capacity nails: 51
- Nail diameter: 2.8 - 3.7 mm
- Nail type: 50 - 90 mm
- Battery type: Li-ion
- Number of batteries: 0
- Weight with battery pack: 5 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



3 249,00 zł **-10%**

**2 924,10 zł** (tax excl.)

(3 596,64 zł (tax incl.))

PayU VISA MasterCard



Product page

link > <https://imilwauke.pl/en/25009-m18-ffn21-0c-framing-nailer-18-v-fuel-in-case-without-equipment-493...>

### DESCRIPTION

- Excellent power to consistently seat nails sub-flush to the surface in hardwoods.
- Ready to Fire Nail Technology eliminates ramp-up time between each nail discharge.
- No gas cartridges and no cleaning required, designed to deliver durability and reliability to the most demanding users with very little maintenance.
- Two mode selection allows for sequential fire for precision or bump fire for speed.
- Tool-free, quick and easy depth adjustment to assure nails are driven sub-flush.
- Dry-Fire lockout stops the tool being fired when there are no nails left in the magazine.
- Fires up to 700 nails per charge on a REDLITHIUM™ 5.0 Ah battery pack for maximum productivity.
- Fires standard framing nails which fits an angled magazine at 20° to 22°.
- Quick access and easy clearing of jams.
- LED work light illuminates the work surface for better placement of nails.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- **Supplied in case (Kitbox) without battery and charger.**

### FEATURES

Symbol	M18FFN21-0C
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność magazynka	51.00
Średnica gwoźdźcia	2.8/3.7