



SYMBOL: **4933478768** MANUFACTURER: **Milwaukee** EAN: **4058546360504**



M18 FPP6H2-502B - POWERPACK M18 FUEL™, M18 FPD2, M18 FIW2F12, M18 CCS55, M18 FSZ, M18 CAG125X, 2 x 5.0 Ah + charger, 4933478768

- M18 FPD2 - M18 FUEL™ percussion drill
- M18 FIW2F12 - M18 FUEL™ 1/2" compact impact wrench with friction ring
- M18 CCS55 - M18 FUEL™ 55 mm circular saw for wood and plastics
- M18 FSZ - M18 FUEL™ SAWZALL™
- M18 CAG125X - M18 FUEL™ 125 mm angle grinder with slide switch
- M18 TLED - M18™ LED torch
- Supplied in bag with 2 batteries and charger.



Product page

link > <https://imilwauke.pl/en/25195-m18-fpp6h2-502b-powerpack-m18-fuel-m18-fpd2-m18-fiw2f12-m18-ccs55-m...>



DESCRIPTION

M18 FPD2

- Voltage: 18 V
- Max. drilling masonry/steel/wood: 16/16/89 mm
- Max. percussion rate: 0 - 32000 bpm
- Max. torque: 135 Nm
- No load speed gear 1/2: 0-550/0-2000 rpm
- Battery type: Li-ion
- Chuck capacity: 13 mm
- Weight with battery pack: 2.2 kg
- Higher power efficiency under load - outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
- Brushless POWERSTATE™ motor for heavy application under load.
- 13 mm metal chuck for quick bit changes and bit retention.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Battery fuel gauge displays remaining charge.
- 40 percent brighter LED workspace illumination - vs previous model.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FIW2F12

- Voltage: 18 V
- Impact rate: 0-1000 / 0-2400 / 0-3400 ipm
- Max. torque: 102 / 203 / 339 / 34 Nm
- Max. fastening torque: 339 Nm
- Nut-busting torque: 339 Nm
- Tool reception: 1/2" square
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack (M18 B5): 1.8 kg
- Power efficiency under load - outstanding torque of 339 Nm.
- Extremely compact design - total length of just 124 mm for access into tight spaces.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops.
- Auto shut-off control applies no more than 34 Nm of torque for hand-tight fastening applications to prevent over tightening.
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- 1/2" square friction ring.
- Reversible belt hook.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 CCS55

- Voltage: 18 V
- No load speed: 5000 rpm
- Blade diameter: 165 mm
- Bore size: 15.87 mm
- Max. cutting depth 90°/45°: 55/41 mm
- Sound power level: 91.8 db(A)
- Sound pressure level: 80.8 dB(A)

- Vibration level: 2.45 m/s²
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2.8 kg
- Brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more cuts per charge.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- 50° bevel capacity.
- Magnesium upper and lower guards provide best in class durability for impact resistance.
- Magnesium shoe reduces weight and maximises durability.
- Integrated dust blower keeps cut line clear.
- Hang hook allows safe storage of the tool.
- Integrated battery fuel gauge & LED light.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Standard equipment: circular saw blade, side fence.

M18 FSZ

- Voltage: 18 V
- Max. cutting depth in aluminium/metal pipe/non-ferrous metal/soft-wood/steel: 25/150/25/300/20 mm
- No load stroke rate: 0-3000 spm
- Stroke length: 32 mm
- Vibration cutting boards: 26.7 m/s²
- Vibration cutting boards uncertainty: 1.5 m/s²
- Vibration cutting wooden beam: 25.1 m/s²
- Vibration cutting wooden beam uncertainty: 1.5 m/s²
- Weight with battery pack (M18 B5): 3.8 kg
- Brushless POWERSTATE™ motor for up to 5x longer motor life and up to 30% faster cutting.
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups.
- Wear resistant lever actuated FIXTEC™ blade clamp provides fast and easy blade changes.
- Metal reinforced battery connection provides improved durability and battery retention over life.
- Built-in LED light illuminates the work surface while cutting.
- Adjustable shoe for optimised use of saw blades.
- Integrated battery fuel gauge.
- Durable metal rafter hang hook for work space management and safety.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 CAG125X

- Voltage: 18 V
- Disc diameter: 125 mm
- Max. cutting depth: 33 mm
- No load speed: 8500 rpm
- Spindle size: M14
- Slide switch
- Brake: no
- FIXTEC: yes
- Line lock out function: yes
- Anti-kickback protection: yes
- Vibration sanding: 1.4 m/s²
- Vibration at grinding metal: 3.4 m/s²
- Sound power level: 94.2 dB(A)
- Sound pressure level: 83.2 dB(A)
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2.5 kg
- Brushless POWERSTATE™ motor with the power to grind and up to 10x more motor life.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Premium gearing system - same system as used at high performance corded grinders.
- 125 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner.
- 100% tool-free wheel change thanks to integrated FIXTEC™ system.
- Slim handle design.
- Removable dust screen to prevent debris entrance, prolonging motor life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Standard equipment: quick release safety guard, AVS side handle, flange, flange nut, spanner, 2x dust screens.

M18 TLED

- Lumens: 120
- Max. run time with M18 B5 battery: 29 h
- Voltage: 18 V
- 135° rotating head
- Bulb type: LED
- Battery type: Li-ion
- Weight with battery pack (M18 B2): 0.7 kg
- The 120 Lumen LED light is 2x brighter and whiter than conventional incandescent bulbs.
- M18™ LED electronics deliver 2x longer run time on a single charge with less heat.
- Sealed aluminium head is designed for impact and weather-resistant durability.
- 135° rotating head allows the user to easily direct the light beam at the desired work area.
- Integrated hook for hands-free use.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

FEATURES

Symbol	M18FPP6H2-502BEU
Opis	wiertarko-wkrętarzka udarowa, klucz udarowy, szlifierka kątowna, piła, pilarka, 2 akumulatory, ładowarka
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.0

