



SYMBOL: **4933478767** MANUFACTURER: **Milwaukee** EAN: **4058546360498**



M18 FPP2T2-502XEU - Set POWERPACK M18 FUEL™, M18 FPD2, M18 FIW2F12, 2 x 5.0 Ah + charger, in case, 4933478767



- Set includes:
 - M18 FPD2 - M18 FUEL™ percussion drill
 - M18 FIW2F12 - M18 FUEL™ 1/2" compact impact wrench
 - M18 B5 - 2 x batteries 5.0 Ah
 - M12-18 FC - charger
- Supplied in case (HD Box) with 2 batteries and charger.



Product page

link > <https://imilwauke.pl/en/25196-m18-fpp2t2-502xeu-set-powerpack-m18-fuel-m18-fpd2-m18-fiw2f12-2-x-5...>



DESCRIPTION

M18 FPD2

- Voltage: 18 V
- Max. drilling masonry/steel/wood: 16/16/89 mm
- Max. percussion rate: 0 - 32000 bpm
- Max. torque: 135 Nm
- No load speed gear 1/2: 0-550/0-2000 rpm
- Battery type: Li-ion
- Chuck capacity: 13 mm
- Weight with battery pack: 2.2 kg
- Higher power efficiency under load - outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
- Brushless POWERSTATE™ motor for heavy application under load.
- 13 mm metal chuck for quick bit changes and bit retention.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Battery fuel gauge displays remaining charge.
- 40 percent brighter LED workspace illumination - vs previous model.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FIW2F12

- Voltage: 18 V
- Impact rate: 0-1000 / 0-2400 / 0-3400 ipm
- Max. torque: 102 / 203 / 339 / 34 Nm
- Max. fastening torque: 339 Nm
- Nut-busting torque: 339 Nm
- Tool reception: 1/2" square
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack (M18 B5): 1.8 kg
- Power efficiency under load - outstanding torque of 339 Nm.
- Extremely compact design - total length of just 124 mm for access into tight spaces.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops.
- Auto shut-off control applies no more than 34 Nm of torque for hand-tight fastening applications to prevent over tightening.
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- 1/2" square friction ring.
- Reversible belt hook.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

FEATURES

Symbol	M18FPP2T2-502XEU
Opis	wiertarko-wkrętarka udarowa, klucz udarowy, 2 akumulatory, ładowarka
Ilość akumulatorów	2



Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.0

