



SYMBOL: **4933479532** MANUFACTURER: **Milwaukee** EAN: **4058546373269**



M18 FPP2AS-553P - Set POWERPACK M18™ FUEL™, M18 ONEFHIWF34, M18 FMTIW2F12, 1 x 5.5 Ah, 2 x 5.0 Ah + charger, in PACKOUT

- Set includes:
- M18 ONEFHIWF34 - 3/4" high torque impact wrench
- M18 FMTIW2F12 - 1/2" mid-torque impact wrench
- Supplied in PACKOUT with 3 batteries and charger.



Product page

link > <https://imilwauke.pl/en/25197-m18-fpp2as-553p-set-powerpack-m18-fuel-m18-onefhiwf34-m18-fmtiw2f12...>

DESCRIPTION

M18 ONEFHIWF34

- Voltage: 18 V
- Max. torque: 702/1138/1627/1627 Nm
- Nut-busting torque: 2034 Nm
- Impact rate: 0-850/0-1850/0-2400/0-2400 ipm
- No load speed: 0-800/0-1300/0-1800/0-1800 rpm
- Max. bolt diameter: M33
- Tool holder: 3/4" square
- Battery type: Li-ion
- Weight with battery pack: 3.5 kg
- The M18 FUEL™ high torque impact wrench with ONE-KEY™ technology delivers 1627 Nm of fastening torque in a compact size of 213 mm, which gives more access in tight spaces.
- The 4 -Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 4 bolt removal, provides a maximum nut-busting torque of 2034 Nm then shifts to 750 rpm for outstanding control when removing fasteners.
- The integrated blow counting sensor enhances the consistent repeatability of the chosen torque setting.
- ONE-KEY™ tool customisation allows the user to optimise their tool for specific applications.
- ONE-KEY™ tool tracking & security offers a cloud-based inventory management platform that supports both location tracking and theft prevention.
- 3/4" friction ring reception.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FMTIW2F12

- Voltage: 18 V
- Max. fastening torque: 745 Nm
- Max. torque: 475/610/745/47 Nm
- No load speed: 0-1200 / 0-1950 / 0-2575 / 0-1325 rpm
- Nut-busting torque: 881 Nm
- Max. bolt diameter: M22
- Impact rate: 0-900 / 0-2100 / 0-3100 ipm
- Tool reception: 1/2" square
- Battery type: Li-ion
- Weight with battery pack: 2.3 kg
- Most versatile cordless impact wrench in the MILWAUKEE® impressive arsenal with an industry-leading performance at 881 Nm of nut-busting torque and 745 Nm of fastening torque.
- Incredibly compact design for this performance level, with only 152 mm overall length ideal for applications in tight spaces.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops.
- Auto shut-off control applies no more than 47 Nm of torque for hand-tight fastening applications to prevent over-tightening.
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- 1/2" square friction ring.
- Reversible belt hook.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

FEATURES

Symbol	M18FPP2AS-553P
Opis	2 klucze udarowe, 3 akumulatory, ładowarka
Ilość akumulatorów	3

Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.0, 5.5

