



SYMBOL: **4933478888** MANUFACTURER: **Milwaukee** EAN: **4058546361709**



M18 FHX-0X - 4-mode 26 mm SDS-Plus Hammer 18 V, FUEL™, in case without equipment, 4933478888

- Voltage: 18 V
- Blow energy: 2.5 J
- Max. percussion rate: 0-4800 bpm
- No load speed: 0-1330 rpm
- Max. drilling wood/steel/concrete: 28/13/26 mm
- Vibration drilling: 12.9 m/s²
- Vibration chiseling: 14.2 m/s²
- Tool reception: SDS-Plus + Reduced shank 13 mm
- Battery type: Li-ion
- Weight with battery pack (M18 HB5.5): 4.5 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~2 319,00 zł~~ **-10%**

2 087,10 zł (tax excl.)

(2 567,13 zł (tax incl.))

PayU

Product page

link > <https://imilwauke.pl/en/25577-m18-fhx-0x-4-mode-26-mm-sds-plus-hammer-18-v-fuel-in-case-without-e...>

DESCRIPTION

- The fastest drilling rotary hammer in its class leading to increased productivity.
- Powerful hammer mechanism delivers 2.5 J of impact energy at low 12.9 m/s² vibrations.
- Drills up to 125 Ø10 x 50 mm holes on a M18™ HIGH OUTPUT™ 5.5 Ah battery charge.
- AUTOSTOP™ shuts down the tool to protect the user of sharp movement in bind up situations.
- FIXTEC™ system for keyless chuck changing between SDS-Plus and 13 mm metal chuck.
- All metal gear case - optimum seating of the gears for enhanced tool life.
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility.
- Compatible with M18 FCDEXL or M18 FDDEXL dust extractors.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Supplied in case (HD Box) without battery and charger.

FEATURES

Symbol	M18FHX-0X
Waga [kg]	4.50
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-4800
Energia uderu	2.50
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	26.00
Średnica wiercenia w drewnie	28.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1330