



SYMBOL: **4933479435** MANUFACTURER: **Milwaukee** EAN: **4058546372293**



## M18 CHPX-802X - High performance 4-mode SDS-Plus hammer 18 V, 8.0 Ah, FUEL™, in case, with 2 batteries and charger, 4933479435

- Voltage: 18 V
- Blow energy: 4.0 J
- Max. percussion rate: 0 - 5000 bpm
- No load speed: 0 - 1350 rpm
- Max. drilling concrete/steel/wood: 28/13/30 mm
- Optimised drilling capacity in concrete: Ø 7 - 22 mm
- Tool reception: SDS-Plus
- Battery type: Li-ion
- No. of batteries supplied: 2
- Battery pack capacity: 8.0 Ah
- Weight with battery pack (M18 HB8): 4.7 kg

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



Product page

link > <https://imilwauke.pl/en/25580-m18-chpx-802x-high-performance-4-mode-sds-plus-hammer-18-v-80-ah-fu...>

### DESCRIPTION

- Milwaukee Tool designed and built brushless POWERSTATE™ motor.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- High powered motor gives corded tool performance.
- Hardest hitting cordless SDS hammer in its class. Powerful hammer mechanism delivers 4.0 J (EPTA) of impact energy at low 8.6 m/s<sup>2</sup> vibrations thanks to the new dual rail anti-vibration system.
- All metal gear case - optimum seating of the gears for enhanced service life.
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility.
- FIXTEC™ system - keyless chuck changing.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Compatible with M18-28 CPDEX dust extractor.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- **Supplied in case (HD Box) with 2 batteries and charger.**

### FEATURES

Symbol	M18CHPX-802X
Waga [kg]	4.70
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-5000
Energia uderu	4.00
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	28.00
Średnica wiercenia w drewnie	30.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1350