



SYMBOL: **4933479903** MANUFACTURER: **Milwaukee** EAN: **4058546376970**



M18 CHD-0 - 4-mode rotary hammer SDS-Plus 18 V, without equipment

NOTE: The product has been withdrawn from sale by the manufacturer. Suggested replacement in the "related products" tab.

- Voltage: 18 V
- Blow energy: 2.3 J
- Max. percussion rate: 0 - 4900 bpm
- No load speed: 0 - 1400 rpm
- Max. drilling wood/steel/concrete: 26/28/13 mm
- Tool reception: SDS-Plus
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack (M18 B4): 4.1 kg



Product page

link > <https://imilwauke.pl/en/25584-m18-chd-0-4-mode-rotary-hammer-sds-plus-18-v-without-equipment.html>



DESCRIPTION

- Brushless POWERSTATE™ motor for up to 2x longer motor life and up to 25% more power.
- REDLINK PLUS™ intelligence system delivers the most advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™ battery pack delivers up to 2.5x more run time, up to 20% more power, up to 2x more battery life and operates better down to -20°C than other lithium-ion technologies.
- Compact, ergonomic design for increased enduser comfort.
- All metal gear case - optimum seating of the gears for enhanced service life.
- 4-mode operation: rotary hammer, hammer only, rotation only and variolock for maximum versatility.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Supplied without battery and charger.

FEATURES

Symbol	M18CHD-0
Waga [kg]	4.10
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-4900
Energia uderu	2.30
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	26.00
Średnica wiercenia w drewnie	28.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-1400