



SYMBOL: **4933479422** MANUFACTURER: **Milwaukee** EAN: **4058546372163**



M18 FPP6K2-502B - POWERPACK M18™, M18 FPD2, M18 FID2, M18 CCS55, M18 FSZ, M18 FSAG125X, M18 TLED, 2 x 5.0 Ah, 4933479422

- Set includes:
 - M18 FPD2 - M18 FUEL™ percussion drill
 - M18 FID2 - M18 FUEL™ 1/4" HEX impact driver
 - M18 CCS55 - M18 FUEL™ 55 mm circular saw for wood and plastics
 - M18 FSZ - M18 FUEL™ SAWZALL™
 - M18 FSAG125X - M18 angle grinder 125 mm
 - M18 TLED - M18™ LED torch
 - M18 B5 - 2 x 5.0 Ah
 - M12-18 FC
- Supplied in bag with 2 batteries and charger.

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page

link > <https://imilwauke.pl/en/25595-m18-fpp6k2-502b-powerpack-m18-m18-fpd2-m18-fid2-m18-ccs55-m18-fsz-m...>

DESCRIPTION

M18 FPD2

- Voltage: 18 V
- Max. drilling masonry/steel/wood: 16/16/89 mm
- Max. percussion rate: 0 - 32000 bpm
- Max. torque: 135 Nm
- No load speed gear 1/2: 0-550/0-2000 rpm
- Battery type: Li-ion
- Chuck capacity: 13 mm
- Weight with battery pack: 2.2 kg
- Higher power efficiency under load - outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
- Brushless POWERSTATE™ motor for heavy application under load.
- 13 mm metal chuck for quick bit changes and bit retention.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Battery fuel gauge displays remaining charge.
- 40 percent brighter LED workspace illumination - vs previous model.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FID2

- Voltage: 18 V
- Impact rate: 1200/3400/4300/0-4300 ipm
- No load speed: 1900/2800/3600/0-3600 rpm
- Max. torque: 119/176/226/0-226 Nm
- Max. fastening torque: 226 Nm
- Max. bolt diameter: M16
- Battery type: Li-ion
- Weight with battery pack: 1.7 kg
- Sound pressure level: 96.75 dB(A)
- Sound power level measured: 107.75 dB(A)
- Higher power efficiency under load - outstanding torque of 226 Nm.
- Faster driving speed vs. previous model - up to 3600 rpm and 4300 ipm.
- Extremely compact design - total length of just 117 mm for access into tight spaces.
- DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 1 for precision work.
- Mode 2 helps prevent damage to fasteners and material.
- Mode 3 delivers maximum performance for the toughest applications.
- Mode 4 is the optimum between precision work and maximum performance and automatically adjusts speed, impacts and torque.
- Brushless POWERSTATE™ motor for heavy application under load.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- 1/4" Hex chuck for quick and easy bit change.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Standard equipment: belt clip and bit holder.

M18 CCS55

- Voltage: 18 V
- No load speed: 5000 rpm
- Blade diameter: 165 mm



- Bore size: 15.87 mm
- Max. cutting depth 90°/45°: 55/41 mm
- Sound power level: 91.8 db(A)
- Sound pressure level: 80.8 dB(A)
- Vibration level: 2.45 m/s²
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2.8 kg
- Brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more cuts per charge.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- 50° bevel capacity.
- Magnesium upper and lower guards provide best in class durability for impact resistance.
- Magnesium shoe reduces weight and maximises durability.
- Integrated dust blower keeps cut line clear.
- Hang hook allows safe storage of the tool.
- Integrated battery fuel gauge & LED light.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Standard equipment: circular saw blade, side fence.

M18 FSZ

- Voltage: 18 V
- Max. cutting depth in aluminium/metal pipe/non-ferrous metal/soft-wood/steel: 25/150/25/300/20 mm
- No load stroke rate: 0-3000 spm
- Stroke length: 32 mm
- Vibration cutting boards: 26.7 m/s²
- Vibration cutting boards uncertainty: 1.5 m/s²
- Vibration cutting wooden beam: 25.1 m/s²
- Vibration cutting wooden beam uncertainty: 1.5 m/s²
- Weight with battery pack (M18 B5): 3.8 kg
- Brushless POWERSTATE™ motor for up to 5x longer motor life and up to 30% faster cutting.
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups.
- Wear resistant lever actuated FIXTEC™ blade clamp provides fast and easy blade changes.
- Metal reinforced battery connection provides improved durability and battery retention over life.
- Built-in LED light illuminates the work surface while cutting.
- Adjustable shoe for optimised use of saw blades.
- Integrated battery fuel gauge.
- Durable metal rafter hang hook for work space management and safety.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FSAG125X

- Voltage: 18 V
- Disc diameter: 125 mm
- Max. cutting depth: 33 mm
- No load speed: 8500 obr/min
- Spindle size: M14
- Switch type: Slide lock-on switch
- Brake: No
- Soft start function: Yes
- Anti-kickback protection: Yes
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2.7 kg
- Delivering corded performance similar to a 1200 W grinder.
- Reduced gearhead size and lower angle of battery slot - for better balance & ergonomics compared to previous model.
- Anti-vibration side handle for lower vibration.
- Integrated FIXTEC™ system for tool-free wheel change.
- Slim handle design.
- Removable dust screen to prevent debris entrance, prolonging motor life.
- 125 mm keyless guard for great cutting capacity and fast guard adjustment without using a key.
- Line-lock-out function to prevent automatic start up.
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 TLED

- Lumens: 120
- Max. run time with M18 B5 battery: 29 h
- Voltage: 18 V
- 135° rotating head
- Bulb type: LED
- Battery type: Li-ion
- Weight with battery pack (M18 B2): 0.7 kg
- The 120 Lumen LED light is 2x brighter and whiter than conventional incandescent bulbs.
- M18™ LED electronics deliver 2x longer run time on a single charge with less heat.
- Sealed aluminium head is designed for impact and weather-resistant durability.
- 135° rotating head allows the user to easily direct the light beam at the desired work area.
- Integrated hook for hands-free use.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

FEATURES

Symbol	M18FPP6K2-502B
Opis	wiertarko-wkrętarka udarowa, zakrętarka udarowa, szlifierka kątowna, piła, pilarka, latarka, 2 akumulatory, ładowarka
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.0

