PARTNER W DOBORZE ROZWIĄZAŃ

TECHNICZNYCH DLA PRZEMYSŁU I MOTORYZACJI



SYMBOL: 4933479423 MANUFACTURER: Milwaukee EAN: 4058546372170 $\star \star \star \star \star$ M18 FPP6L2-502B - POWERPACK M18™ M18 FPD2, M18 FIW2F12, M18 CCS55, M18 FSZ, M18 FSAG125X, M18 TLED, 2 x 5.0Ah, 4933479423

link > https://imilwauke.pl/en/25596-m18-fpp6l2-502b-powerpack-m18-m18-fpd2-m18-fiw2f12-m18-ccs55-m18-fs..

Set includes:

- M18 FPD2 M18 FUEL[™] percussion drill
- M18 FIW2F12 M18 FUEL[™] Compact impact wrench with friction ring 1/2"
- M18 CCS55 M18 FUEL™ 55 mm circular saw for wood and plastics
- M18 FSZ M18 FUEL[™] SAWZALL[™]
- M18 FSAG125X M18 angle grinder 125 mm
- M18 TLED M18[™] LED torch
- M18 B5 2 x 5.0 Ah
- M12-18 FC
- · Supplied in bag with 2 batteries and charger.

U WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)

Milwaukee



DESCRIPTION

M18 FPD2 Voltage: 18 V

- Max. drilling masonry/steel/wood: 16/16/89 mm
- Max. percussion rate: 0 32000 bpm
- Max. torque: 135 Nm
- No load speed gear 1/2: 0-550/0-2000 rpm
- Battery type: Li-ion
- Chuck capacity: 13 mm • Weight with battery pack: 2.2 kg
- Higher power efficiency under load outstanding torque of 135 Nm. · Extremely compact design of 175 mm length for access into tight spaces
- Advanced heavy duty chuck providing increased bit grip.
- Brushless POWERSTATE™ motor for heavy application under load.
- 13 mm metal chuck for quick bit changes and bit retention.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
 Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Battery fuel gauge displays remaining charge.
- · 40 percent brighter LED workspace illumination vs previous model.
- All metal reversible belt clip to hang your tool quickly and easily
- Flexible battery system: works with all MILWAUKEE® M18[™] batteries

M18 FIW2F12

- Voltage: 18 V
 Impact rate: 0-1000 / 0-2400 / 0-3400 ipm
- Max. torque: 102 / 203 / 339 / 34 Nm
 Max. fastening torque: 339 Nm
- Nut-busting torque: 339 Nm
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 1.8 kg • Power efficiency under load - outstanding torque of 339 Nm.
- Extremely compact design total length of just 124 mm for access into tight spaces.
- · 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility
- · Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops
- · Auto shut-off control applies no more than 34 Nm of torque for hand-tight fastening applications to prevent over tightening
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- Reversible belt hook
- The DNA of our FUEL[™] platform redefines the balance of cordless technologies.
 MILWAUKEE®'s POWERSTATE[™] brushless motor, REDLITHIUM[™] battery pack and REDLINK PLUS[™] electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18[™] batteries

M18 CCS55

- Voltage: 18 V
- No load speed: 5000 rpm
 Blade diameter: 165 mm
- Bore size: 15.87 mm • Max. cutting depth 90°/45°: 55/41 mm
- · Sound power level: 91.8 db(A)
- Vibration level: 2.45 m/s²



Battery type: Li-ion

- Weight with battery pack (M18 B5): 2.8 kg Brushless POWERSTATE[™] motor for up to 3x longer motor life and up to 2x more cuts per charge.
- REDLINK PLUS Tintelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load • REDLITHIUM *-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 50° bevel capacity.
- Magnesium upper and lower guards provide best in class durability for impact resistance.
- Magnesium shoe reduces weight and maximises durability.
- Integrated dust blower keeps out line clear.
- Hang hook allows safe storage of the tool
- Integrated battery fuel gauge & LED light.
 Flexible battery system: works with all MILWAUKEE® M18[™] batteries. · Standard equipment: circular saw blade, side fence

M18 FSZ

Voltage: 18 V

- Max. cutting depth in aluminium/metal pipe/non-ferrous metal/soft-wood/steel: 25/150/25/300/20 mm
- No load stroke rate: 0-3000 spm
- Vibration cutting boards: 26.7 m/s²
- Vibration cutting boards uncertainty: 1.5 m/s²
 Vibration cutting wooden beam: 25.1 m/s²
- Vibration cutting wooden beam uncertainty: 1.5 m/s²
- Weight with battery pack (M18 B5): 3.8 kg
- Brushless POWERSTATE™ motor for up to 5x longer motor life and up to 30% faster cutting.
- Patented gear protecting clutch extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups.
 Wear resistant lever actuated FIXTEC[™] blade clamp provides fast and easy blade changes.
- Metal reinforced battery connection provides improved durability and battery retention over life.
 Built-in LED light illuminates the work surface while cutting.
- · Adjustable shoe for optimised use of saw blades.
- Integrated battery fuel gauge.

- Unregiance Database processing of gauge.
 Durable metal rafter hang hook for work space management and safety.
 The DNA of our FUEL[™] platform redefines the balance of cordless technologies.
 MILWAUKEE®'S POWERSTATE[™] brushless motor, REDLITHIUM[™] battery pack and REDLINK PLUS[™] electronic intelligence delivering outstanding power, run time and durability.

M18 FSAG125X

- Voltage: 18 V Disc diameter: 125 mm
- Max. cutting depth: 33 mm
 No load speed: 8500 obr/min
- Spindle size: M14
- Switch type: Slide lock-on switch
- Brake: No Soft start function: Yes
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2.7 kg
- Delivering corded performance similar to a 1200 W grinder
- Reduced gearhead size and lower angle of battery slot for better balance & ergonomics compared to previous model.
- Anti-vibration side handle for lower vibration.
- Integrated FIXTEC[™] system for tool-free wheel change.
- Slim handle design.
- Removable dust screen to prevent debris entrance, prolonging motor life. • 125 mm keyless guard for great cutting capacity and fast guard adjustment without using a key.
- Line-lock-out function to prevent automatic start up.
 Integrates three MILWAUKEE®-exclusive technologies the POWERSTATE[™] brushless motor, REDLITHIUM[™] battery pack and
- REDLINK PLUS™ intelligence hardware and software which deliver outstanding power, run time and durability on the jobsite
- Flexible battery system: works with all MILWAUKEE® M18[™] batteries.

M18 TLED

- Lumens: 120 • Max. run time with M18 B5 battery: 29 h
- Voltage: 18 V
- Bulb type: LED
- Weight with battery pack (M18 B2): 0.7 kg
- The 120 Lumen LED light is 2x brighter and whiter than conventional incandescent bulbs.
 M18™ LED electronics deliver 2x longer run time on a single charge with less heat.
- Sealed aluminium head is designed for impact and weather-resistant durability
- · 135° rotating head allows the user to easily direct the light beam at the desired work area.
- Integrated hook for hands-free use
- Flexible battery system: works with all MILWAUKEE® M18[™] batteries.

FFATURES

Symbol	M18FPP6L2-502B
Opis	wiertarko-wkrętarka udarowa, klucz udarowy, szlifierka kątowa, piła, pilarka, latarka, 2 akumulatory, ładowarka
llość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.0