



SYMBOL: **4933479535** MANUFACTURER: **Milwaukee** EAN: **4058546373290**



M18 FPP4A2-553P - POWERPACK M18™, M18 FPD2, M18 FMTIW2F12, M18 FHX, M18 FSAG125X, 3 x 5.5Ah+ charger, in PACKOUT, 4933479535

NOTE: The product has been withdrawn from sale by the manufacturer. No suggested replacements available.

- Set includes:
 - M18 FPD2 - Percussion drill 18 V, FUEL™
 - M18 FMTIW2F12 - 1/2" Impact wrench, 745 Nm, 18 V, FUEL™
 - M18 FHX - Hammer drills SDS-Plus 18 V, FUEL™
 - M18 FSAG125X - Angle grinder 125 mm, 18 V
 - M18 HB5.5 - 3 x 5.5 Ah
 - M12-18 FC
- Supplied in PACKOUT.



Product page

link > <https://imilwauke.pl/en/25597-m18-fpp4a2-553p-powerpack-m18-m18-fpd2-m18-fmtiw2f12-m18-fhx-m18-fs...>

DESCRIPTION

M18 FPD2

- Voltage: 18 V
- Max. drilling masonry/steel/wood: 16/16/89 mm
- Max. percussion rate: 0 - 32000 bpm
- Max. torque: 135 Nm
- No load speed gear 1/2: 0-550/0-2000 rpm
- Battery type: Li-ion
- Chuck capacity: 13 mm
- Weight with battery pack: 2.2 kg

- Higher power efficiency under load - outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
- Brushless POWERSTATE™ motor for heavy application under load.
- 13 mm metal chuck for quick bit changes and bit retention.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Battery fuel gauge displays remaining charge.
- 40 percent brighter LED workspace illumination - vs previous model.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FMTIW2F12

- Voltage: 18 V
- Max. torque: 475/610/745/47 Nm
- Impact rate: 0-900/0-2100/0-3100 ipm
- No load speed: 0-1250/0-1950/0-2575/0-1325 rpm
- Nut-busting torque: 881 Nm
- Max. bolt diameter: M22
- Tool reception: 1/2" square
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2.3 kg

- Most versatile cordless impact wrench in the MILWAUKEE® impressive arsenal with an industry-leading performance at 881 Nm of nut-busting torque and 745 Nm of fastening torque.
- Incredibly compact design for this performance level, with only 152 mm overall length ideal for applications in tight spaces.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops.
- Auto shut-off control applies no more than 47 Nm of torque for hand-tight fastening applications to prevent over-tightening.
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- 1/2" square friction ring.
- Reversible belt hook.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FHX

- Voltage: 18 V
- Blow energy: 2.5 J
- Max. percussion rate: 0-4800 bpm



- No load speed: 0-1330 rpm
- Max. drilling wood/steel/concrete: 28/13/26 mm
- Vibration drilling: 12.9 m/s²
- Vibration chiseling: 14.2 m/s²
- Tool reception: SDS-Plus + Reduced shank 13 mm
- Battery type: Li-ion
- Weight with battery pack (M18 HB5.5): 4.5 kg

- The fastest drilling rotary hammer in its class leading to increased productivity.
- Powerful hammer mechanism delivers 2.5 J of impact energy at low 12.9 m/s² vibrations.
- Drills up to 125 Ø10 x 50 mm holes on a M18™ HIGH OUTPUT™ 5.5 Ah battery charge.
- AUTOSTOP™ shuts down the tool to protect the user of sharp movement in bind up situations.
- FIXTEC™ system for keyless chuck changing between SDS-Plus and 13 mm metal chuck.
- All metal gear case - optimum seating of the gears for enhanced tool life.
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility.
- Compatible with M18 FCDDEXL or M18 FDDEXL dust extractors.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.

M18 FSAG125X

- Voltage: 18 V
- Disc diameter: 125 mm
- Max. cutting depth: 33 mm
- No load speed: 8500 obr/min
- Spindle size: M14
- Switch type: Slide lock-on switch
- Brake: No
- Soft start function: Yes
- Anti-kickback protection: Yes
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2,7 kg

- Delivering corded performance similar to a 1200 W grinder.
- Reduced gearhead size and lower angle of battery slot - for better balance & ergonomics compared to previous model.
- Anti-vibration side handle for lower vibration.
- Integrated FIXTEC™ system for tool-free wheel change.
- Slim handle design.
- Removable dust screen to prevent debris entrance, prolonging motor life.
- 125 mm keyless guard for great cutting capacity and fast guard adjustment without using a key.
- Line-lock-out function to prevent automatic start up.
- Integrates three MILWAUKEE®-exclusive technologies - the POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ intelligence hardware and software - which deliver outstanding power, run time and durability on the jobsite.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

- Supplied in case (PACKOUT) with 3 batteries and charger.

FEATURES

Symbol	M18FPP4A2-553P
Opis	wiertarko-wkrętarka udarowa, klucz udarowy, szlifierka kątowna, młot, 3 akumulatory, ładowarka
Ilość akumulatorów	3
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.5