



SYMBOL: **4933479536** MANUFACTURER: **Milwaukee** EAN: **4058546373306**



M18 FPP4B2-533P - POWERPACK M18™, M18 FPD2, M18 FID2, M18 FHX, 2 x 5.5 Ah, 1 x 3.0 Ah + charger, 4933479536

- Set includes:
 - M18 FPD2 - M18 FUEL™ percussion drill
 - M18 FID2 - M18 FUEL™ 1/4" HEX impact driver
 - M18 FHX - M18 FUEL™ hammer drills SDS-Plus
 - M18 ONEFSAG125XB - M18 FUEL™, ONE-KEY™, angle grinder 125 mm
 - M18 HB5.5 - 2 x 5.5 Ah
 - M18 HB3 - 1 x 3.0 Ah
 - M12-18 FC
 - Supplied in PACKOUT.

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



Product page

link > <https://imilwauke.pl/en/25598-m18-fpp4b2-533p-powerpack-m18-m18-fpd2-m18-fid2-m18-fhx-2-x-55-ah-1...>



DESCRIPTION

M18 FPD2

- Voltage: 18 V
- Max. drilling masonry/steel/wood: 16/16/89 mm
- Max. percussion rate: 0 - 32000 bpm
- Max. torque: 135 Nm
- No load speed gear 1/2: 0-550/0-2000 rpm
- Battery type: Li-ion
- Chuck capacity: 13 mm
- Weight with battery pack: 2.2 kg

- Higher power efficiency under load - outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
- Brushless POWERSTATE™ motor for heavy application under load.
- 13 mm metal chuck for quick bit changes and bit retention.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Battery fuel gauge displays remaining charge.
- 40 percent brighter LED workspace illumination - vs previous model.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FID2

- Voltage: 18 V
- Impact rate: 1200/3400/4300/0-4300 ipm
- No load speed: 1900/2800/3600/0-3600 rpm
- Max. torque: 119/176/226/0-226 Nm
- Max. fastening torque: 226 Nm
- Max. bolt diameter: M16
- Battery type: Li-ion
- Weight with battery pack: 1.7 kg

- Sound pressure level: 96.75 dB(A)
- Sound power level measured: 107.75 dB(A)
- Higher power efficiency under load - outstanding torque of 226 Nm.
- Faster driving speed vs. previous model - up to 3600 rpm and 4300 ipm.
- Extremely compact design - total length of just 117 mm for access into tight spaces.
- DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 1 for precision work.
- Mode 2 helps prevent damage to fasteners and material.
- Mode 3 delivers maximum performance for the toughest applications.
- Mode 4 is the optimum between precision work and maximum performance and automatically adjusts speed, impacts and torque.
- Brushless POWERSTATE™ motor for heavy application under load.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- 1/4" Hex chuck for quick and easy bit change.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.
- Standard equipment: belt clip and bit holder.

M18 FHX

- Voltage: 18 V
- Blow energy: 2.5 J

- Max. percussion rate: 0-4800 bpm
- No load speed: 0-1330 rpm
- Max. drilling wood/steel/concrete: 28/13/26 mm
- Vibration drilling: 12.9 m/s²
- Vibration chiseling: 14.2 m/s²
- Tool reception: SDS-Plus + Reduced shank 13 mm
- Battery type: Li-ion
- Weight with battery pack (M18 HB5.5): 4.5 kg

- The fastest drilling rotary hammer in its class leading to increased productivity.
- Powerful hammer mechanism delivers 2.5 J of impact energy at low 12.9 m/s² vibrations.
- Drills up to 125 Ø10 x 50 mm holes on a M18™ HIGH OUTPUT™ 5.5 Ah battery charge.
- AUTOSTOP™ shuts down the tool to protect the user of sharp movement in bind up situations.
- FIXTEC™ system for keyless chuck changing between SDS-Plus and 13 mm metal chuck.
- All metal gear case - optimum seating of the gears for enhanced tool life.
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility.
- Compatible with M18 FCDDEXL or M18 FDDEXL dust extractors.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.

M18 ONEFSAG125XB

- Voltage: 18 V
- Disk diameter: 125 mm
- No load speed: 8500 rpm
- Max. cutting depth: 33 mm
- Switch type: slide lock-on switch
- Brake: yes
- FIXTEC™: yes
- Anti-kickback protection: yes
- Line lock out function: yes
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2.7 kg

- Delivering corded performance similar to a 1200 W grinder.
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools. ONE-KEY™ also features a remote locking functionality.
- RAPIDSTOP™ for fastest disc brake in less than 2 seconds and best user protection.
- Reduced gearhead size and lower angle of battery slot - for better balance & ergonomics compared to previous model.
- Anti-vibration side handle for lower vibration.
- Integrated FIXTEC™ system for tool-free wheel change.
- Slim handle design.
- Removable dust screen to prevent debris entrance, prolonging motor life.
- 125 mm keyless guard for great cutting capacity and fast guard adjustment without using a key.
- Line-lock-out function to prevent automatic start up.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

- Supplied in case (PACKOUT) with 3 batteries and charger.

FEATURES

Symbol	M18FPP4B2-533P
Opis	wiertarko-wkrętarka udarowa, zakrętarka udarowa, szlifierka kątowna, miot, 3 akumulatory, ładowarka
Ilość akumulatorów	3
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	3,0, 5,5

