



SYMBOL: **4933480555** MANUFACTURER: **Milwaukee** EAN: **4058546408404**



M12 FPP7A-624P - POWERPACK M12™, M12 FPD, M12 FID, M12 FCOT, M12 CH, M12 FMT, M12 JS, M12 PAL, 2 x 2.0, 2 x 6.0 Ah, 4933480555

• Set includes:

- M12 FPD
- M12 FID
- M12 FCOT
- M12 CH
- M12 FMT
- M12 JS
- M12 PAL
- 2 x 2.0 Ah
- 2 x 6.0 Ah
- C12 C



Product page

link > <https://imilwauke.pl/en/25602-m12-fpp7a-624p-powerpack-m12-m12-fpd-m12-fid-m12-fcot-m12-ch-m12-fm...>

DESCRIPTION

M12 FPD

- Voltage: 12 V
- No load speed gear 1/2: 0-450/0-1700 rpm
- Max. percussion rate: 0-25500 bpm
- Max. torque: 44 Nm
- Chuck capacity: 13 mm
- Max. drilling wood/ metal/ masonry: 35/13/13 mm
- Wood screws to: 8 mm
- Battery type: Li-ion
- Weight with battery pack: 1.2/1.5 kg

- Brushless POWERSTATE™ motor delivers more power in a more compact size.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- 13 mm metal chuck for quick bit changes and bit retention.
- Electronic clutch with 16 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer.
- Fuel gauge displays remaining charge.
- Bright LED workspace illumination.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

M12 FID

- Voltage: 12 V
- Impact rate: 0-4000 ipm
- No load speed: 0-1300/0-2400/0-3300/0-3300 rpm
- Max. torque: 147 Nm
- Max. bolt diameter: M14
- Sound pressure level: 88.1 dB(A)
- Sound power level measured: 99.1 dB(A)
- Battery type: Li-ion
- Weight with battery pack: 1.1 kg

- Brushless POWERSTATE™ motor with faster speed in a more compact size of 130 mm.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- 4-Mode DRIVE CONTROL allows the user to shift to three different speed and torque settings, as well as a self-tapping mode to maximise application versatility.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- 1/4" Hex chuck for quick and easy bit change.
- On board fuel gauge and LED light.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

M12 FCOT

- Voltage: 12 V
- Disc diameter: 76 mm
- Bore size: 10 mm
- Max. cutting depth: 16.3 mm
- No load speed: 20000 rpm
- Anti-kickback protection: no
- Battery type: Li-ion
- Weight with battery pack: 1.1 kg

- Fast accurate cutting with up to 20000 RPM.



- Optimised ergonomic design for best control and one-handed use.
- Only 1.1 kg and 226 mm in length.
- Multi-material cutting capability with variety of blades available (metal cut-off wheel, carbide abrasive blade and diamond tile blade).
- A very capable problem solving tool for cutting steel, stainless steel, non-ferrous materials, drywall, fibre cement, plastic and ceramics.
- Easily adjustable guard and unique forward/reverse selectable blade rotation direction to protect user from debris in various cutting positions.
- Quick release dust shoe with depth adjustment and optional dust extraction port.
- Brushless POWERSTATE™ motor delivers more power in a more compact size.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- 76 mm blade offers up to 16.3 mm depth of cut.
- Fuel gauge displays remaining charge.
- Brightest LED workspace illumination.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

M12 CH

- Voltage: 12 V
- Blow energy: 1.1 J
- Full load hammer action: 0-6575 bpm
- No load speed: 0-900 rpm
- Max. drilling wood/steel/concrete: 13/10/13 mm
- Optimised drilling capacity in concrete: Ø 5.5 - 12 mm
- Battery type: Li-ion
- Weight with battery pack (M12 B2): 1.7 kg

- Industry's first brushless compact 12V rotary hammer with 1.1 Joules (EPTA), 0 - 6575 bpm & 0 - 900 rpm.
- Exceptionally low vibration value 4.4 m/s² can be used for 8 hours in a day.
- Will drill over 60 50 mm x 6 mm holes per battery charge.
- Superior power to weight ratio in its class with brushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more run time.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- 2-mode operation: choose rotary hammer or rotation only for maximum versatility.
- Optimised hammer drilling up to 6 - 10 mm (max 13 mm).
- 43 mm neck size - compatible with M12 DE dust extractor.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

M12 FMT

- Voltage: 12 V
- No load speed: 10000 - 20000 rpm
- Oscillation angle left/right: 1.8°
- Vibration cutting wood: 10.01 m/s²
- Vibration cutting wood uncertainty: 1.5 m/s²
- Battery type: Li-ion
- Weight with battery pack: 1.6 kg

- Brushless POWERSTATE™ motor delivers fast cutting speed through common materials without slowing or bogging down in hardwoods.
- Adjustable 10,000 to 20,000 opm allow the user to get the perfect cut whatever the material.
- Lowest vibration in its class, 4.56 m/s² driving productivity through performance and safety.
- 1.8° left/right oscillation angle allowing faster cuts.
- Ability to make up to 59 cuts in oak on one 2.0 Ah battery charge.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- FIXTEC™ tool free blade change with universal blade change adaptor included to accept all major competitor blades.
- LED work light illuminates the cut line in low light conditions.
- Supplied with an adapter, plunge cut blade OSC 112, sanding backing pad, 5 x sanding sheets and a DEK26 dust guard to use when sanding.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

M12 JS

- Voltage: 12 V
- Stroke length: 19 mm
- No load stroke rate: 0 - 2800 spm
- Max. cutting capacity wood/aluminium: 40/15 mm
- Vibration cutting wood/metal: 10.1/7.8 m/s²
- Bevel capacity: 45°
- Battery type: Li-ion
- Weight: 1.8 kg
- Weight with battery pack: 2.1 kg

- Sound power and pressure level: 88.5 / 77.5 dB(A)
- New grip design combines the best features from both top handle and barrel grip jigsaw design.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- Variable speed - electronic trigger provides user flexibility and control.
- Smooth cut - minimal vibration during cutting provides ultra smooth performance.
- Precision roller guide increases user control and reduces blade deviation.
- Line of sight - the compact tool design improves cut line visibility.
- Tool free bevel facility - quick and easy bevel adjustment up to 45°.
- QUIK-LOK™ T-Shank blade clamp.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- On board fuel gauge and LED light.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

M12 PAL

- Voltage: 12 V
- Max. lumens: 250/700
- Max. run time with M12 B4 battery: 24/8 h
- IP protection class: IP54
- Bulb type: LED
- Battery type: Li-ion
- Weight with battery pack (M12 B4): 0.9 kg

- TRUEVIEW™ high definition lighting with up to 700 lumens.
- Up to 24 hours of run time on M12™ 4.0 Ah battery pack.
- With powerful magnets as well as a rotating light head design with 110° rotation in each direction to provide multiple beam options.
- Highly durable and impact resistant design to withstand drops up to 3 m.
- Most compact M12™ flood light designed for the on-the-go needs of service and maintenance trades.
- 2.1 AMP USB output for USB device charging.
- IP54 rating, the light is protected from dust and splashing water.
- Low battery indicator, light flashes when battery pack is low on charge.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

• Supplied in 2 cases (PACKOUT) with 4 batteries and charger.

FEATURES

Symbol	M12FPP7A-624P
--------	---------------



Opis	wiertarko-wkrętarka udarowa, zakrętarka udarowa, szlifierka kątowa, młot, narzędzie wielofunkcyjne, wyrzynarka, lampa, 4 akumulatory, ładowarka
Ilość akumulatorów	4
Zasilanie	battery
Napięcie akumulatora [V]	12
Pojemność akumulatora [Ah]	2.0, 6.0

