



SYMBOL: **4933479537** MANUFACTURER: **Milwaukee** EAN: **4058546373313**



## M18 PP8A-586P - POWERPACK M18™, M18 FDD2, M18 FID2, M18 CAG125X, M18 BLCS66, M18 FMT, M18 FSZ, M18 TLED

- Set includes:
- M18 FDD2 - M18 FUEL™ drill driver
- M18 FID2 - M18 FUEL™ 1/4" Hex impact driver
- M18 CAG125X - M18 FUEL™ 125 mm angle grinder with slide switch
- M18 BLCS66 - M18™ brushless 66 mm circular saw for wood and plastics
- M18 FMT - M18 FUEL™ multi-tool
- M18 FSZ - M18 FUEL™ SAWZALL™
- M18 TLED - M18™ LED torch
- 1 x M18 HB8
- 2 x M18 HB5.5
- 3 x M18 B5
- M18 DFC



Product page

link > <https://imilwauke.pl/en/25641-m18-pp8a-586p-powerpack-m18-m18-fdd2-m18-fid2-m18-cag125x-m18-blcs66...>

### DESCRIPTION

#### M18 FDD2

- Voltage: 18 V
- No load speed gear 1/2: 0-550/0-2000 rpm
- Max. torque: 135 Nm
- Chuck capacity: 13 mm
- Speed settings: 2
- Max. drilling wood/ metal: 89/16 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 2.1 kg
- Higher power efficiency under load - outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
- Brushless POWERSTATE™ motor for heavy application under load.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Battery fuel gauge displays remaining charge.
- 40 percent brighter LED workspace illumination - vs previous model.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

#### M18 FID2

- Voltage: 18 V
- Impact rate: 1200/3400/4300/0-4300 ipm
- No load speed: 1900/2800/3600/0-3600 rpm
- Max. torque: 119/176/226/0-226 Nm
- Max. fastening torque: 226 Nm
- Max. bolt diameter: M16
- Battery type: Li-ion
- Weight with battery pack: 1.7 kg
- Sound pressure level: 96.75 dB(A)
- Sound power level measured: 107.75 dB(A)
- Higher power efficiency under load - outstanding torque of 226 Nm.
- Faster driving speed vs. previous model - up to 3600 rpm and 4300 ipm.
- Extremely compact design - total length of just 117 mm for access into tight spaces.
- DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Mode 1 for precision work.
- Mode 2 helps prevent damage to fasteners and material.
- Mode 3 delivers maximum performance for the toughest applications.
- Mode 4 is the optimum between precision work and maximum performance and automatically adjusts speed, impacts and torque.
- Brushless POWERSTATE™ motor for heavy application under load.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- 1/4" Hex chuck for quick and easy bit change.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

#### M18 CAG125X

- Voltage: 18 V
- Disc diameter: 125 mm
- Max. cutting depth: 33 mm



- No load speed: 8500 rpm
- Spindle size: M14
- Slide switch
- Brake: no
- FIXTEC: yes
- Line lock out function: yes
- Anti-kickback protection: yes
- Vibration sanding: 1.4 m/s<sup>2</sup>
- Vibration at grinding metal: 3.4 m/s<sup>2</sup>
- Sound power level: 94.2 dB(A)
- Sound pressure level: 83.2 dB(A)
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2.5 kg
- Brushless POWERSTATE™ motor with the power to grind and up to 10x more motor life.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Premium gearing system - same system as used at high performance corded grinders.
- 125 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner.
- 100% tool-free wheel change thanks to integrated FIXTEC™ system.
- Slim handle design.
- Removable dust screen to prevent debris entrance, prolonging motor life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 BLCS66

- Voltage: 18 V
- No load speed: 5000 rpm
- Blade diameter: 190 mm
- Bore size: 30 mm
- Max. cutting depth 90°: 66 mm
- Max. cutting depth 45°: 48 mm
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 4 kg
- M18™ brushless circular saw with a 190 mm blade giving a 66 mm depth of cut which enables the saw to cut three stacked 19 mm OSB boards.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Durable metal rafter hang hook for work space management and safety.
- Vacuum adaptor supplied fits directly to all MILWAUKEE® dust extractors.
- Pressed aluminum shoe for maximum durability.
- Integrated LED light for workspace illumination.
- 50° bevel capacity with a 46 mm depth of cut.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FMT

- Voltage: 18 V
- Oscillation angle left/right: 2.1°
- No load speed: 10000 - 20000 rpm
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 1.9 kg
- POWERSTATE™ brushless motor pairs with an aggressive oscillation angle of 2.1° (left/ right) and 10,000 – 20,000 OPM to deliver one of the fastest cut speeds in the industry.
- Suitable for many demanding applications with ease, such as rip cuts through hardwoods and nail embedded wood.
- 10-setting dial with an auto-load feature allows users to adjust the speed to the application.
- FIXTEC™ tool free blade change with universal blade change adaptor included to accept all major competitor blades.
- Integrated 180 degree LED light for maximum visibility in low-light situations.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FSZ

- Voltage: 18 V
- Max. cutting depth in aluminium/metal pipe/non-ferrous metal/soft-wood/steel: 25/150/25/300/20 mm
- No load stroke rate: 0-3000 spm
- Stroke length: 32 mm
- Vibration cutting boards: 26.7 m/s<sup>2</sup>
- Vibration cutting boards uncertainty: 1.5 m/s<sup>2</sup>
- Vibration cutting wooden beam: 25.1 m/s<sup>2</sup>
- Vibration cutting wooden beam uncertainty: 1.5 m/s<sup>2</sup>
- Weight with battery pack (M18 B5): 3.8 kg
- Brushless POWERSTATE™ motor for up to 5x longer motor life and up to 30% faster cutting.
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups.
- Wear resistant lever actuated FIXTEC™ blade clamp provides fast and easy blade changes.
- Metal reinforced battery connection provides improved durability and battery retention over life.
- Built-in LED light illuminates the work surface while cutting.
- Adjustable shoe for optimised use of saw blades.
- Integrated battery fuel gauge.
- Durable metal rafter hang hook for work space management and safety.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 TLED

- Lumens: 120
- Max. run time with M18 B5 battery: 29 h
- Voltage: 18 V
- 135° rotating head
- Bulb type: LED
- Battery type: Li-ion
- Weight with battery pack (M18 B2): 0.7 kg
- The 120 Lumen LED light is 2x brighter and whiter than conventional incandescent bulbs.
- M18™ LED electronics deliver 2x longer run time on a single charge with less heat.
- Sealed aluminium head is designed for impact and weather-resistant durability.
- 135° rotating head allows the user to easily direct the light beam at the desired work area.
- Integrated hook for hands-free use.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

• Supplied in case and bag with 6 batteries and charger.

FEATURES

Symbol	M18PP8A-586P
Opis	wiertarko-wkrętarka, zakrętarka udarowa, szlifierka kątowna, piła, pilarka, narzędzie wielofunkcyjne, latarka, 6 akumulatorów, ładowarka
Ilość akumulatorów	6



Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.0, 5.5, 8.0