
# PARTNER W DOBORZE ROZWIĄZAŃ

TECHNICZNYCH DLA PRZEMYSŁU I MOTORYZACJI





#### SYMBOL: 4933479537 MANUFACTURER: Milwaukee $\star \star \star \star \star$ FAN: 4058546373313 M18 PP8A-586P - POWERPACK M18<sup>™</sup>, M18 FDD2, M18 FID2, M18 CAG125X, M18 BLCS66, M18 FMT, M18 FSZ, M18 TLED, 4933479537

## Set includes:

- M18 FDD2 M18 FUEL<sup>™</sup> drill driver
- M18 FID2 M18 FUEL™ 1/4" Hex impact driver
- M18 CAG125X M18 FUEL<sup>™</sup> 125 mm angle grinder with slide switch
- M18 BLCS66 M18™ brushless 66 mm circular saw for wood and plastics
- M18 FMT M18 FUEL<sup>™</sup> multi-tool
- M18 FSZ M18 FUEL<sup>™</sup> SAWZALL<sup>™</sup>
- M18 TLED M18<sup>™</sup> LED torch
- 1 x M18 HB8
- 2 x M18 HB5.5
- 3 x M18 B5
- M18 DFC

Milwaukee



link > https://imilwauke.pl/en/25641-m18-pp8a-586p-powerpack-m18-m18-fdd2-m18-fid2-m18-cag125x-m18-blcs6..

# DESCRIPTION

# M18 FDD2

• Voltage: 18 V

- No load speed gear 1/2: 0-550/0-2000 rpm
- Max. torque: 135 Nm
- Chuck capacity: 13 mm Speed settings: 2
- Max. drilling wood/ metal: 89/16 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack: 2.1 kg
- Higher power efficiency under load outstanding torque of 135 Nm.
   Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
  Brushless POWERSTATE™ motor for heavy application under load.
- REDLINK PLUS<sup>™</sup> intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
   REDLITHIUM<sup>™</sup>-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- · Battery fuel gauge displays remaining charge.
- 40 percent brighter LED workspace illumination vs previous model
- All metal reversible belt clip to hang your tool quickly and easily.
   Flexible battery system: works with all MILWAUKEE® M18™ batteries

# M18 FID2

- Voltage: 18 V
- Impact rate: 1200/3400/4300/0-4300 ipm No load speed: 1900/2800/3600/0-3600 rpm
- Max. torque: 119/176/226/0-226 Nm
- Max. fastening torque: 226 Nm
   Max. bolt diameter: M16
- Battery type: Li-ion
- Weight with battery pack: 1.7 kg
- Sound pressure level: 96.75 dB(A)
- Sound power level measured: 107.75 dB(A)
- Higher power efficiency under load outstanding torque of 226 Nm
- Faster driving speed vs. previous model up to 3600 rpm and 4300 ipm.
   Extremely compact design total length of just 117 mm for access into tight spaces
- Mode 1 for precision work.
- Mode 2 helps prevent damage to fasteners and material.
- · Mode 4 is the optimum between precision work and maximum performance and automatically adjusts speed, impacts and torque.
- Brushless POWERSTATE™ motor for heavy application under load.
- REDLINK PLUS<sup>™</sup> intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.

- M18 CAG125X
- Voltage: 18 V
- Disc diameter: 125 mm • Max. cutting depth: 33 mm

- Mode 3 delivers maximum performance for the toughest applications.

- REDLITHIUM"-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 1/4" Hex chuck for quick and easy bit change
- Flexible battery system: works with all MILWAUKEE® M18<sup>™</sup> batteries.

No load speed: 8500 rpm

- Spindle size: M14
- Brake: no
- FIXTEC: yes
- · Line lock out function: yes
- Anti-kickback protection: yes
   Vibration sanding: 1.4 m/s<sup>2</sup>
- Vibration at grinding metal: 3.4 m/s<sup>2</sup>
- Sound power level: 94.2 dB(A)
- Sound pressure level: 83.2 dB(A)
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2.5 kg
- Brushless POWERSTATE<sup>™</sup> motor with the power to grind and up to 10x more motor life.
   REDLINK PLUS<sup>™</sup> intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM\* ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- 125 mm keyless guard great cutting capacity and fast guard adjustment without using a spanner
- Slim handle design.
- Removable dust screen to prevent debris entrance, prolonging motor life.
   Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

# M18 BLCS66

- Voltage: 18 V No load speed: 5000 rpm
- Blade diameter: 190 mm
- Bore size: 30 mm
- Max. cutting depth 90°: 66 mm Max. cutting depth 45°: 48 mm
- Battery type: Li-ion
- M18" brushless circular saw with a 190 mm blade giving a 66 mm depth of cut which enables the saw to cut three stacked 19 mm OSB boards.
- REDLINK<sup>™</sup> overload protection electronics in tool and battery pack deliver best in class system durability.
- REDLITHIUM<sup>™</sup> battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Durable metal rafter hang hook for work space management and safety.
   Vacuum adaptor supplied fits directly to all MILWAUKEE® dust extractors.
- Pressed aluminum shoe for maximum durability.
  Integrated LED light for workspace illumination.
- 50° bevel capacity with a 46 mm depth of cut
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

## M18 FMT

- Voltage: 18 V
   Oscillation angle left/right: 2,1°
- No load speed: 10000 20000 rpm
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 1,9 kg
- POWERSTATE<sup>TH</sup> brushless motor pairs with an aggressive oscillation angle of 2.1° (left/ right) and 10,000 20,000 OPM to deliver one of the fastest cut speeds in the industry
- Suitable for many demanding applications with ease, such as rip cuts through hardwoods and nail embedded wood.
- FIXTEC™ tool free blade change with universal blade change adaptor included to accept all major competitor blades.
- Integrated 180 degree LED light for maximum visibility in low-light situations.
   The DNA of our FUEL<sup>™</sup> platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE<sup>™</sup> brushless motor, REDLITHIUM<sup>™</sup> battery pack
- and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

# M18 FSZ

- Voltage: 18 V
- Max. cutting depth in aluminium/metal pipe/non-ferrous metal/soft-wood/steel: 25/150/25/300/20 mm
- No load stroke rate: 0-3000 spm
- Vibration cutting boards: 26.7 m/s<sup>2</sup> Vibration cutting boards uncertainty: 1.5 m/s<sup>2</sup>
- Vibration cutting wooden beam: 25.1 m/s<sup>2</sup>
- Vibration cutting wooden beam uncertainty: 1.5 m/s<sup>2</sup> Weight with battery pack (M18 B5): 3.8 kg

- Brushless POWERSTATE<sup>™</sup> motor for up to 5x longer motor life and up to 30% faster cutting.
  Patented gear protecting clutch extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups.
  Wear resistant lever actuated FIXTEC<sup>™</sup> blade clamp provides fast and easy blade changes.
  Metal reinforced battery connection provides improved durability and battery retention over life.

- · Built-in LED light illuminates the work surface while cutting
- Adjustable shoe for optimised use of saw blades.
- Integrated battery fuel gauge.
- Durable metal rafter hang hook for work space management and safety.
- Durable metal rater right from row work space management and success.
   The DNA of our FUEL™ platform redefines the balance of cordless technologies.
   MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
   MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
   MILWAUKEE® sectors and the sector of the secto
- Flexible battery system: works with all MILWAUKEE® M18<sup>™</sup> batteries.

M18 TLED

- Max. run time with M18 B5 battery: 29 h
- Voltage: 18 V • 135° rotating head
- Bulb type: LED
- Battery type: Li-ion
- Weight with battery pack (M18 B2): 0.7 kg
- The 120 Lumen LED light is 2x brighter and whiter than conventional incandescent bulbs.
- M18™ LED electronics deliver 2x longer run time on a single charge with less heat.
- Sealed aluminium head is designed for impact and weather-resistant durability.
- · 135° rotating head allows the user to easily direct the light beam at the desired work area.
- Integrated hook for hands-free use
- Flexible battery system: works with all MILWAUKEE® M18<sup>™</sup> batteries.

# Supplied in case and bag with 6 batteries and charger.

# FEATURES

Symbol	M18PP8A-586P
Opis	wiertarko-wkrętarka, zakrętarka udarowa, szlifierka kątowa, piła, pilarka, narzędzie wielofunkcyjne, latarka, 6 akumulatorów, ładowarka
Ilość akumulatorów	6

Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	5.0, 5.5, 8.0



