



SYMBOL: **4933479538** MANUFACTURER: **Milwaukee** EAN: **4058546373320**



M18 PP8B-586P - POWERPACK M18™, M18 HOAL, M18 FSZ, M18 FMT, M18 FPD2, M18 FIW2F12, M18 CAG125X, M18 BLCS66

- Set includes:
- M18 HOAL - high output area light
- M18 FSZ - SAWZALL™
- M18 FMT - multi-tool
- M18 FPD2 - percussion drill
- M18 FIW2F12 - 1/2" compact impact wrench with friction ring
- M18 CAG125X - 125 mm angle grinder with slide switch
- M18 BLCS66 - brushless 66 mm circular saw for wood and plastics
- 2 x M18 HB8
- 2 x M18 HB5.5
- 2 x M18 HB3
- M12-18 FC
- M1418 C6



Product page

link > <https://imilwauke.pl/en/25642-m18-pp8b-586p-powerpack-m18-m18-hoal-m18-fsz-m18-fmt-m18-fpd2-m18-f...>

DESCRIPTION

M18 HOAL

- Voltage (DC): 18 V
- Voltage (AC): 110 - 240 V
- Max. lumens: 1200/2000/4000 lumens
- Max. run time with M18 B5 battery: 12/6/3 h
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 3.3 kg
- 4000 lumens TRUEVIEW™ of High Definition Output.
- Up to 12 hours of run time on M18™ REDLITHIUM™ 5.0 Ah battery pack.
- 120° rotatable light head and integrated key holes for horizontal and vertical hanging.
- Impact resistant design and durable roll cage to protect the light from rough jobsite conditions.
- AC/DC versatility: Powered by MILWAUKEE® M18™ batteries, or mains plug supply.
- Easy one-handed transport with built-in carry handles.
- Low battery indicator, light flashes when battery pack is low on charge.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FSZ

- Voltage: 18 V
- Max. cutting depth in aluminium/metal pipe/non-ferrous metal/soft-wood/steel: 25/150/25/300/20 mm
- No load stroke rate: 0-3000 spm
- Stroke length: 32 mm
- Vibration cutting boards: 26.7 m/s²
- Vibration cutting boards uncertainty: 1.5 m/s²
- Vibration cutting wooden beam: 25.1 m/s²
- Vibration cutting wooden beam uncertainty: 1.5 m/s²
- Weight with battery pack (M18 B5): 3.8 kg
- Brushless POWERSTATE™ motor for up to 5x longer motor life and up to 30% faster cutting.
- Patented gear protecting clutch - extends gear and motor life by absorbing high impact forces caused by sudden blade lock-ups.
- Wear resistant lever actuated FIXTEC™ blade clamp provides fast and easy blade changes.
- Metal reinforced battery connection provides improved durability and battery retention over life.
- Built-in LED light illuminates the work surface while cutting.
- Adjustable shoe for optimised use of saw blades.
- Integrated battery fuel gauge.
- Durable metal rafter hang hook for work space management and safety.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FMT

- Voltage: 18 V
- Oscillation angle left/right: 2,1°
- No load speed: 10000 - 20000 rpm
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 1.9 kg
- POWERSTATE™ brushless motor pairs with an aggressive oscillation angle of 2.1° (left/ right) and 10,000 – 20,000 OPM to deliver one of the fastest cut speeds in the industry.
- Suitable for many demanding applications with ease, such as rip cuts through hardwoods and nail embedded wood.
- 10-setting dial with an auto-load feature allows users to adjust the speed to the application.
- FIXTEC™ tool free blade change with universal blade change adaptor included to accept all major competitor blades.
- Integrated 180 degree LED light for maximum visibility in low-light situations.



- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FPD2

- Voltage: 18 V
- Max. drilling masonry/steel/wood: 16/16/89 mm
- Max. percussion rate: 0 - 32000 bpm
- Max. torque: 135 Nm
- No load speed gear 1/2: 0-550/0-2000 rpm
- Speed settings: 2
- Chuck capacity: 13 mm
- Weight with battery pack (M18 B5): 2.2 kg
- Higher power efficiency under load - outstanding torque of 135 Nm.
- Extremely compact design of 175 mm length for access into tight spaces.
- Advanced heavy duty chuck providing increased bit grip.
- Brushless POWERSTATE™ motor for heavy application under load.
- 13 mm metal chuck for quick bit changes and bit retention.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Battery fuel gauge displays remaining charge.
- 40 percent brighter LED workspace illumination - vs previous model.
- All metal reversible belt clip to hang your tool quickly and easily.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 FIW2F12

- Voltage: 18 V
- Impact rate: 0-1000/0-2400/0-3400 ipm
- Max. torque: 102/203/339/34 Nm
- Max. fastening torque: 339 Nm
- Nut-busting torque: 339 Nm
- Tool reception: 1/2" square
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack (M18 B5): 1.8 kg
- Power efficiency under load - outstanding torque of 339 Nm.
- Extremely compact design - total length of just 124 mm for access into tight spaces.
- 4-Mode DRIVE CONTROL allows the user to shift into four different speed and torque settings to maximise application versatility.
- Bolt removal control delivers full torque output, then decreases RPMs once the bolt is loosened to prevent fastener drops.
- Auto shut-off control applies no more than 34 Nm of torque for hand-tight fastening applications to prevent over tightening.
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- 1/2" square friction ring.
- Reversible belt hook.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 CAG125X

- Voltage: 18 V
- Disc diameter: 125 mm
- Max. cutting depth: 33 mm
- No load speed: 8500 rpm
- Spindle size: M14
- Slide switch
- Brake: no
- FIXTEC: yes
- Line lock out function: yes
- Anti-kickback protection: yes
- Vibration sanding: 1.4 m/s²
- Vibration at grinding metal: 3.4 m/s²
- Sound power level: 94.2 dB(A)
- Sound pressure level: 83.2 dB(A)
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 2.5 kg
- Brushless POWERSTATE™ motor with the power to grind and up to 10x more motor life.
- REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Premium gearing system - same system as used at high performance corded grinders.
- 125 mm keyless guard - great cutting capacity and fast guard adjustment without using a spanner.
- 100% tool-free wheel change thanks to integrated FIXTEC™ system.
- Slim handle design.
- Removable dust screen to prevent debris entrance, prolonging motor life.
- Individual battery cell monitoring optimises tool run time and ensures long term pack durability.
- Fuel gauge displays remaining charge.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

M18 BLCS66

- Voltage: 18 V
- No load speed: 5000 rpm
- Blade diameter: 190 mm
- Bore size: 30 mm
- Max. cutting depth 90°: 66 mm
- Max. cutting depth 45°: 48 mm
- Battery type: Li-ion
- Weight with battery pack (M18 B5): 4 kg
- M18™ brushless circular saw with a 190 mm blade giving a 66 mm depth of cut which enables the saw to cut three stacked 19 mm OSB boards.
- REDLINK™ overload protection electronics in tool and battery pack deliver best in class system durability.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Durable metal rafter hang hook for work space management and safety.
- Vacuum adaptor supplied fits directly to all MILWAUKEE® dust extractors.
- Pressed aluminum shoe for maximum durability.
- Integrated LED light for workspace illumination.
- 50° bevel capacity with a 46 mm depth of cut.
- Flexible battery system: works with all MILWAUKEE® M18™ batteries.

- SAWZALL™ sabre saw blade set - 10 pcs.
- SDS-Plus MX4 drill bit set and Shockwave™ impact bit set - 32 pieces

- Supplied in case and bag with 6 batteries and 2 chargers.

FEATURES

Symbol	M18PP8B-586P
Opis	wiertarko-wkrętarka, klucz udarowy, szlifierka kątowna, piła, pilarka, narzędzie wielofunkcyjne, lampa, 6 akumulatorów, 2 ładowarki

7-05-2024



kontakt@imilwauke.pl



12 415-80-81, 790 680 540

Ilość akumulatorów	6
Zasilanie	battery
Napięcie akumulatora [V]	18
Pojemność akumulatora [Ah]	3.0, 5.5, 8.0

