



SYMBOL: **4933478884** MANUFACTURER: **Milwaukee** EAN: **4058546361662**



M18 ONEFHP-0X - High performance 4-mode 32 mm SDS-Plus hammer 18 V, FUEL™, ONE-KEY™, in case, without equipment, 4933478884

- Voltage: 18 V
- Blow energy: 5 J
- No load speed: 0 - 800 rpm
- Max. percussion rate: 0 - 4600 bpm
- Max. drilling concrete/steel/wood: 32/13/30 mm
- Max. drilling tunnel bit: 75 mm
- Battery type: Li-ion
- No. of batteries supplied: 0
- Weight with battery pack (M18 HB5.5): 5 kg

WARRANTY: WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~2 869,00 zł~~ **-10%**

2 582,10 zł (tax excl.)

(3 175,98 zł (tax incl.))



Product page

link > <https://imilwauke.pl/en/26227-m18-onefhp-0x-high-performance-4-mode-32-mm-sds-plus-hammer-18-v-fu...>

DESCRIPTION

- Vibration drilling: 6.9 m/s²
- Vibration chiseling: 7.4 m/s²
- Sound pressure level: 95.1 dB(A)
- Sound power level: 106.1 dB(A)

- Hardest hitting cordless SDS-Plus hammer in its class.
- Powerful hammer mechanism delivers 5.0 J (EPTA) of impact energy at low 6.9 m/s² vibrations.
- Drills up to 10 Ø18 x 100 mm holes on a M18™ HIGH OUTPUT™ 5.5 Ah battery charge.
- AUTOSTOP™ shuts down the tool to protect the user of sharp movement in bind up situations.
- ONE-KEY™ tool tracking & security offers a free of charge cloud-based tracking network and inventory management platform for your tools.
- ONE-KEY™ also features a remote locking functionality.
- All metal gear case - optimum seating of the gears for enhanced tool life.
- 4-mode operation: rotary hammer, hammer only, rotation only and selectable work position of the chisel (variolock) for maximum versatility
- Compatible with M18 FPDEXL dust extractor.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- The HIGH OUTPUT™ system of tools elevates the M18 FUEL™ technologies to a new level and delivers extended performance and extended run time.
- These tools are designed to maximise the partnership with HIGH OUTPUT™ batteries.
- Supplied in case (HD Box) without battery and charger.

FEATURES

Symbol	M18ONEFHP-0X
Waga [kg]	5.00
Uchwyt	SDS-Plus
Częstość uderu [ud/min]	0-4600
Energia uderu	5.00
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	18
Średnica wiercenia w betonie	32.00
Średnica wiercenia w drewnie	30.00
Średnica wiercenia w metalu	13.00
Obroty [obr/min]	0-800