



SYMBOL: **4933479867** MANUFACTURER: **Milwaukee promo** EAN: **4058546376611**



M12 FPD2-0 - Sub compact percussion drill 12 V, FUEL™, without equipment, 4933479867

- Voltage: 12 V
- Max. percussion rate: 0-22500 bpm
- Max. torque: 45 Nm
- Max. drilling wood/steel/masonry: 35/13/13 mm
- No load speed gear 1/gear 2: 0-450/0-1550 rpm
- Chuck capacity: 13 mm
- Speed settings: 2
- Wood screws to: 8 mm
- Battery type: Li-ion
- Weight with battery pack (M12 B6): 1.4 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



849,00 zł **-33%**

568,67 zł (tax excl.)

(699,46 zł (tax incl.))



Product page

link > <https://imilwauke.pl/en/26737-m12-fpd2-0-sub-compact-percussion-drill-12-v-fuel-without-equipment...>

DESCRIPTION

- Vibration drilling into concrete/metal: 15.73/1.92 m/s²
- Vibration screw driving: 0.86 m/s²
- Sound pressure level (LPA): 89.3 dB(A)
- Sound power level (LWA): 100 dB(A)
- Extremely compact design of 152 mm length for access into tight spaces.
- 45 Nm of torque - superior power to size ratio.
- 13 mm heavy duty metal chuck for quick bit changes and bit retention.
- Mechanical clutch with 13 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer.
- On board fuel gauge, metal belt clip and LED light.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.
- Supplied without battery and charger.

FEATURES

Symbol	M12FPD2-0
Typ	udarowa
Nm max	45.00
Częstość udaru [ud/min]	0-22500
Ilość akumulatorów	brak
Ilość biegów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Średnica uchwytu wiertarskiego	13.00
Średnica wiercenia w drewnie	35.00
Średnica wiercenia w metalu	13.00
Średnica wiercenia w murze	13.00
Obroty [obr/min]	0-450/0-1550