



SYMBOL: **4933479876** MANUFACTURER: **Milwaukee** EAN: **4058546376703**



M12 FID2-0 - Sub compact 1/4" impact driver 12 V, FUEL™, without equipment

- Voltage: 12 V
- Max. torque: 170 Nm
- Impact rate: 0-4000 ipm
- No load speed: 0-1700/0-2900/0-3600/0-3600 rpm
- Chuck capacity: 1/4" Hex
- Vibration level: 14.35 m/s²
- Vibration uncertainty: 1.5 m/s²
- Sound pressure level (LPA): 99.25 dB(A)
- Sound power level (LWA): 110.25 dB(A)
- No. of batteries supplied: 0
- Battery type: Li-ion
- Weight with battery pack (M12 B6): 1.1 kg

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



~~849,00 zł~~ **-10%**

764,10 zł (tax excl.)

(939,84 zł (tax incl.))

PayU



Product page

link > <https://imilwauke.pl/en/26738-m12-fid2-0-sub-compact-14-impact-driver-12-v-fuel-without-equipment...>

DESCRIPTION

- The compact design with a length of only 127 mm is ideal for working in confined spaces.
- Outstanding power to size ratio with 170 Nm of torque.
- Fast driving speed with up to 3,600 rpm and 4,000 ipm.
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- 4-Mode DRIVE CONTROL allows the user to shift to three different speed and torque settings, as well as a self-tapping mode to maximise application versatility.
- 1/4" Hex chuck for quick and easy bit change.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.
- **Supplied without battery and charger.**

FEATURES

Symbol	M12FID2-0
Wyjście	1/4"
Nm max	170
Częstość uderu [ud/min]	0-4000
Ilość akumulatorów	brak
Zasilanie	battery
Napięcie akumulatora [V]	12
Obroty [obr/min]	0-1700/0-2900/0-3600/0-3600

