







MANUFACTURER: Milwaukee EAN: 4058546376710



M12 FID2-202X - Sub compact 1/4" impact driver HEX 12 V, 2.0 Ah, FUEL™, in case, with 2 batteries and charger, 4933479877

- · Voltage: 12 V
- Max. torque: 170 Nm
- Impact rate: 0-4000 ipm
- No load speed: 0-1700/0-2900/0-3600/0-3600 rpm
- Chuck capacity: 1/4" Hex
- · Vibration level: 14.35 m/s²
- Vibration uncertainty: 1.5 m/s²
- Sound pressure level (LPA): 99.25 dB(A)
- Sound power level (LWA): 110.25 dB(A)
- No. of batteries supplied: 2
- Battery type: Li-ion
- Weight with battery pack (M12 B2): 0.9 kg


















1 187,10 zł (tax excl.) (1 460,13 zł (tax incl.))

1 319,00 zł -10%



link > https://imilwauke.pl/en/26764-m12-fid2-202x-sub-compact-14-impact-driver-hex-12-v-20-ah-fuel-in-c.

## DESCRIPTION

- The compact design with a length of only 127 mm is ideal for working in confined spaces
- Outstanding power to size ratio with 170 Nm of torque. Fast driving speed with up to 3,600 rpm and 4,000 ipm.
- Tri-LEDs deliver high definition lighting to increase workspace visibility.
- · 4-Mode DRIVE CONTROL allows the user to shift to three different speed and torque settings, as well as a self-tapping mode to maximise application versatility. • 1/4" Hex chuck for quick and easy bit change
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
  Flexible battery system: works with all MILWAUKEE® M12™ batteries.
- Supplied in case (HD Box) with 2 batteries and charger.

## FEATURES

FEATURES	
Symbol	M12FID2-202X
Wyjście	1/4"
Nm max	170
Częstość udaru [ud/min]	0-4000
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Obroty [obr/min]	0-1700/0-2900/0-3600/0-3600

