







MANUFACTURER: Milwaukee EAN: 4058546374754

M12 FDSS-422X - Sub compact spot sander 12 V, 2.0 and 4.0 Ah, FUEL™, in case, with 2 batteries and charger, 4933479681

- · Voltage: 12 V
- No load speed: 0-8000/0-10000/0-12000/0-14000 rpm
- Oscillation diameter: 1.5 mm
- Sanding pad size: 88.8 x 63.5 mm
- Vibration sanding: 4.3 m/s²
- Vibration sanding uncertainty: 1.5 m/s²
- Sound power level (LWA): 75.7 dB(A)
- Sound pressure level (LPA): 64.7 dB(A)
- No. of batteries supplied: 2
- · Battery type: Li-ion
- Weight with battery pack (M12 B2): 0.8 kg

















1 304,10 zł (tax excl.)

(1 604,04 zł (tax incl.))



Pavu VISA MasterCard

link > https://imilwauke.pl/en/26766-m12-fdss-422x-sub-compact-spot-sander-12-v-20-and-40-ah-fuel-in-cas...

DESCRIPTION

- · Compact detail sander with a penta shaped pad allows uncompromised corner accessibility.
- · Four speed modes allows the correct speed to be set for different types of material.
- Low vibration at only 4.3 m/s²
- Sponge interface pad included optimises the tool for profiles and contours which increases the precision and removal of material.
- · Hook and loop pad allows the user to change quickly between different grit types.
- LED lights up your work area for better visibility.
- The DNA of our FUEL." platform redefines the balance of cordless technologies. MILWAUKEE@'s POWERSTATE" brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MII WAUKEE® M12™ batteries.
- Supplied in case (HD Box) with 2 batteries and charger.

-EATORES	
Symbol	M12FDSS-422X
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12