





SYMBOL: 4933480588

MANUFACTURER: Milwaukee

EAN: **4058546408732**

M12 FPP2A2-602X - POWERPACK M12™ FUEL™, M12 FPD2, M12 FID2, 2 x 6.0 Ah + charger, in case, 4933480588

- · Set includes:
- M12 FPD2 percussion drill
- M12 FID2 1/4" impact driver
- M12 B6 2 x batteries 6.0 Ah
- C12 C charger
- · Supplied in case (HD Box).

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



2 389,00 zł -10%

2 150,10 zł (tax excl.)

(2 644,62 zł (tax incl.))

Pavu VISA MasterCard





link > https://imilwauke.pl/en/26794-m12-fpp2a2-602x-powerpack-m12-fuel-m12-fpd2-m12-fid2-2-x-60-ah-char...

DESCRIPTION

M12 FPD2

- · Voltage: 12 V Max. percussion rate: 0-22500 bpm
- · Max. torque: 45 Nm
- Max. drilling wood/steel/masonry: 35/13/13 mm
- No load speed gear 1/gear 2: 0-450/0-1550 rpm
 Chuck capacity: 13 mm
- Speed settings: 2
- · Wood screws to: 8 mm
- Weight with battery pack (M12 B6): 1.4 kg
- Vibration drilling into concrete/metal: 15.73/1.92 m/s²
- Vibration screw driving: 0.86 m/s²
 Sound pressure level (LPA): 89.3 dB(A)
- · Sound power level (LWA): 100 dB(A)
- Extremely compact design of 152 mm length for access into tight spaces.
- 45 Nm of torque superior power to size ratio.
- Mechanical clutch with 13 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer
- On board fuel gauge, metal belt clip and LED light.
 The DNA of our FUEL™ platform redefines the balance of cordless technologies
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.

 Flexible battery system: works with all MILWAUKEE® M12™ batteries.

M12 FID2

- Voltage: 12 V

 Max. torque: 170 Nm · Impact rate: 0-4000 ipm
- No load speed: 0-1700/0-2900/0-3600/0-3600 rpm
- Chuck capacity: 1/4" Hex
 Vibration level: 14.35 m/s²
- Vibration uncertainty: 1.5 m/s²
 Sound pressure level (LPA): 99.25 dB(A)
- Sound power level (LWA): 110.25 dB(A)
- Battery type: Li-ion
 Weight with battery pack (M12 B6): 1.1 kg
- The compact design with a length of only 127 mm is ideal for working in confined spaces.
- Outstanding power to size ratio with 170 Nm of torque.
- Fast driving speed with up to 3,600 rpm and 4,000 ipm.
- · 4-Mode DRIVE CONTROL allows the user to shift to three different speed and torque settings, as well as a self-tapping mode to maximise application versatility
- 1/4" Hex chuck for guick and easy bit change.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies. MILWAUKEE®'s POWERSTATE™ brushless motor,
- REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

Supplied in case (HD Box) with 2 batteries and charger.



FEATURES

Symbol	M12FPP2A2-602X
Opis	wiertarko-wkrętarka udarowa, zakrętarka udarowa, 2 akumulatory, ładowarka
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Pojemność akumulatora [Ah]	6.0