





SYMBOL: 4933480590

MANUFACTURER: Milwaukee

EAN: 4058546408756

M12 FPP2F2-402X - POWERPACK M12™ FUEL™, M12 FPD2, M12 CH, 2 x 4.0 Ah + charger, in case, 4933480590

- · Set includes:
- M12 FPD2 percussion drill
- M12 CH SDS-Plus hammer
- M12 B4 2 x batteries 4.0 Ah
- C12 C charger
- · Supplied in case (HD Box).

WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)



link > https://imilwauke.pl/en/26797-m12-fpp2f2-402x-powerpack-m12-fuel-m12-fpd2-m12-ch-2-x-40-ah-charge...



DESCRIPTION

M12 FPD2

- · Voltage: 12 V Max. percussion rate: 0-22500 bpm
- · Max. torque: 45 Nm
- Max. drilling wood/steel/masonry: 35/13/13 mm
- No load speed gear 1/gear 2: 0-450/0-1550 rpm
 Chuck capacity: 13 mm
- Speed settings: 2
- · Wood screws to: 8 mm
- Weight with battery pack (M12 B6): 1.4 kg
- Vibration drilling into concrete/metal: 15.73/1.92 m/s²
- Vibration screw driving: 0.86 m/s²
 Sound pressure level (LPA): 89.3 dB(A)
- · Sound power level (LWA): 100 dB(A)
- Extremely compact design of 152 mm length for access into tight spaces. • 45 Nm of torque - superior power to size ratio.

- Mechanical clutch with 13 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer
- On board fuel gauge, metal belt clip and LED light.
 The DNA of our FUEL™ platform redefines the balance of cordless technologies
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.

 Flexible battery system: works with all MILWAUKEE® M12™ batteries.

M12 CH

- Voltage: 12 V Blow energy: 1.1 J Full load hammer action: 0-6575 bpm
- No load speed: 0-900 rpm
- Max. drilling wood/steel/concrete: 13/10/13 mm
 Optimised drilling capacity in concrete: Ø 5.5 12 mm
- · Weight with battery pack (M12 B2): 1.7 kg
- Industry's first brushless compact 12V rotary hammer with 1.1 Joules (EPTA), 0 6575 bpm & 0 900 rpm.
- Exceptionally low vibration value 4.4 m/s² can be used for 8 hours in a day.
- Will drill over 60 50 mm x 6 mm holes per battery charge.
- Superior power to weight ratio in its class with bushless POWERSTATE™ motor for up to 3x longer motor life and up to 2x more run time.
 REDLINK PLUS™ intelligence system delivers an advanced digital overload protection for tool and battery and uniquely enhances the tool performance under load.
- REDLITHIUM™ battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life
- · 2-mode operation: choose rotary hammer or rotation only for maximum versatility
- Optimised hammer drilling up to 6 10 mm (max 13 mm)
- 43 mm neck size compatible with M12 DE dust extractor
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

Supplied in case (HD Box) with 2 batteries and charger.

FEATURES



Symbol	M12FPP2F2-402X
Opis	wiertarko-wkrętarka udarowa, młot, 2 akumulatory, ładowarka
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Pojemność akumulatora [Ah]	4.0