



**PARTNER W DOBORZE ROZWIĄZAŃ**  
TECHNICZNYCH DLA PRZEMYSŁU I MOTORYZACJI



Home > Combo kits



SYMBOL: **4933480593**

MANUFACTURER: **Milwaukee**

EAN: **4058546408787**



## M12 FPP2D2-422X - POWERPACK M12™, M12 FPD2, M12 BPRT, 2.0 and 4.0 Ah + charger, in case, 4933480593

- Set includes:
- M12 FPD2 - percussion drill
- M12 BPRT - subcompact rivet tool
- M12 B2, M12 B4 - 2 batteries 2.0 and 4.0 Ah
- C12 C - charger
- Supplied in case (HD Box).

**WARRANTY: EXTENDED WARRANTY (UPON ONLINE REGISTRATION)**



~~2 529,00 zł~~ **-10%**

**2 276,10 zł** (tax excl.)

(2 799,60 zł (tax incl.))

PayU

Product page

link > <https://imilwauke.pl/en/26800-m12-fpp2d2-422x-powerpack-m12-m12-fpd2-m12-bprt-20-and-40-ah-charge...>

### DESCRIPTION

#### M12 FPD2

- Voltage: 12 V
- Max. percussion rate: 0-22500 bpm
- Max. torque: 45 Nm
- Max. drilling wood/steel/masonry: 35/13/13 mm
- No load speed gear 1/gear 2: 0-450/0-1550 rpm
- Chuck capacity: 13 mm
- Speed settings: 2
- Wood screws to: 8 mm
- Battery type: Li-ion
- Weight with battery pack (M12 B6): 1.4 kg
- Vibration drilling into concrete/metal: 15.73/1.92 m/s<sup>2</sup>
- Vibration screw driving: 0.86 m/s<sup>2</sup>
- Sound pressure level (LPA): 89.3 dB(A)
- Sound power level (LWA): 100 dB(A)
- Extremely compact design of 152 mm length for access into tight spaces.
- 45 Nm of torque - superior power to size ratio.
- 13 mm heavy duty metal chuck for quick bit changes and bit retention.
- Mechanical clutch with 13 torque settings, plus 1 for locked clutch drilling and 1 for locked clutch hammer.
- On board fuel gauge, metal belt clip and LED light.
- The DNA of our FUEL™ platform redefines the balance of cordless technologies.
- MILWAUKEE®'s POWERSTATE™ brushless motor, REDLITHIUM™ battery pack and REDLINK PLUS™ electronic intelligence delivering outstanding power, run time and durability.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

#### M12 BPRT

- Voltage: 12 V
- Stroke length: 20.32 mm
- Rivet diameter range: 2.4 - 4.8 mm
- Max. pulling force: 9000 N
- Battery type: Li-ion
- Dimensions: 273 x 66 x 8 x 230 mm
- Weight with battery pack: 2.1 kg
- Sound power and pressure level: 64.1 / 53.1 dB(A)
- Up to 325 x 4.8 mm stainless steel rivets on a single charge with a 2.0 Ah battery pack.
- Suitable for all aluminium, steel, stainless steel and copper rivets up to 4.8 mm.
- Rivets in one stroke with a 20.32 mm stroke length.
- Retention nose pieces hold rivets in any orientation.
- Tool-free access to easily clean jaws. On-board nose piece storage and removal tool for user convenience.
- On board fuel gauge and LED light for added user convenience and illumination in low lit working conditions.
- Ergonomic design with 273 mm H x 66.8 mm W x 165 mm in length without mandrel collector.
- Integrated belt hook and lanyard tie off point.
- REDLITHIUM™-ION battery pack provides superior pack construction, electronics and fade-free performance to deliver more run time and more work over pack life.
- Flexible battery system: works with all MILWAUKEE® M12™ batteries.

Supplied in case (HD Box) with 2 batteries and charger.

### FEATURES

28-04-2025



[kontakt@imilwauke.pl](mailto:kontakt@imilwauke.pl)



12 415-80-81, 790 680 540

Symbol	M12FPP2D2-422X
Opis	wiertarko-wkrętarka udarowa, nitownica, 2 akumulatory, ładowarka
Ilość akumulatorów	2
Zasilanie	battery
Napięcie akumulatora [V]	12
Pojemność akumulatora [Ah]	2.0, 4.0

